- COPY 1-

#### **BID FORM**

Section 1 – Schedule of Prices

Company:	DAK	Truck Co.	
1 7		(	·

Project: Log Loader/Dump Truck, ITB - 4499

Base Bid - Log Loader/Dump Truck and All Required Accessories

For all the equipment and work outlined in these documents for the Log Loader/Dump Truck procurement, complete as specified, using equipment and materials only of the type and manufacturers where specifically named and delivered to the City of Ann Arbor.

**Total Bid Price:** 

(\$ 215,994.00

· Includes GaliON Dump + HoisT.

o option for Warren Hoist... Add \$3,762.00.

option for FreightLine ... Deduct (\$4,100.00)

## CITY OF ANN ARBOR DECLARATION OF COMPLIANCE

#### Non-Discrimination Ordinance

The "non discrimination by city contractors" provision of the City of Ann Arbor Non-Discrimination Ordinance (Ann Arbor City Code Chapter 112, Section 9:158) requires all contractors proposing to do business with the City to treat employees in a manner which provides equal employment opportunity and does not discriminate against any of their employees, any City employee working with them, or any applicant for employment on the basis of actual or perceived age, arrest record, color, disability, educational association, familial status, family responsibilities, gender expression, gender identity, genetic information, height, HIV status, marital status, national origin, political beliefs, race, religion, sex, sexual orientation, source of income, veteran status, victim of domestic violence or stalking, or weight. It also requires that the contractors include a similar provision in all subcontracts that they execute for City work or programs.

In addition the City Non-Discrimination Ordinance requires that all contractors proposing to do business with the City of Ann Arbor must satisfy the contract compliance administrative policy adopted by the City Administrator. A copy of that policy may be obtained from the Purchasing Manager

#### The Contractor agrees:

- (a) To comply with the terms of the City of Ann Arbor's Non-Discrimination Ordinance and contract compliance administrative policy.
- (b) To post the City of Ann Arbor's Non-Discrimination Ordinance Notice in every work place or other location in which employees or other persons are contracted to provide services under a contract with the City.
- (c) To provide documentation within the specified time frame in connection with any workforce verification, compliance review or complaint investigation.
- (d) To permit access to employees and work sites to City representatives for the purposes of monitoring compliance, or investigating complaints of non-compliance.

The undersigned states that he/she has the requisite authority to act on behalf of his/her employer in these matters and has offered to provide the services in accordance with the terms of the Ann Arbor Non-Discrimination Ordinance. The undersigned certifies that he/she has read and is familiar with the terms of the Non-Discrimination Ordinance, obligates the Contractor to those terms and acknowledges that if his/her employer is found to be in violation of Ordinance it may be subject to civil penalties and termination of the awarded contract.

Company Name

Signature of Authorized Representative

Edward Merrill ESOD (Sales)

Print Name and Title

3020 Snow Rd Lansing MI 48917

Address, City, State, Zip

217-144-2749

Questions about the Notice or the City Administrative Policy, Please contact:
Procurement Office of the City of Ann Arbor
(734) 794-6500

Revised 3/31/15 Rev. 0

## LEGAL STATUS OF BIDDER

(The Bidder shall fill out the appropriate form and strike out the other three.)

Bidder declares that it is:

* A corporation organized and doing business under the laws of the State of
Michigan, for whom Edward Merrill, bearing the office title
of Sales, whose signature is affixed to this Bid, is authorized to execute contracts
NOTE: If not incorporated in Michigan, please attach the corporation's Certificate of Authority
A limited liability company doing business under the laws of the State of, whom bearing the title of whose signature is affixed to this proposal, is authorized to exercise contract on behalf of the LLC.
* A partnership, organized under the laws of the State of and filed in the county of, whose members are (list all members and the street and mailing address of each) (attach separate sheet if necessary):
* An individual, whose signature with address, is affixed to this Bid:
Authorized Official (initial here)  5-1-17 V  Date 2-8, 2017
Date 2 - 8 , 2017
Print) Name Hourd Merrill Title Sales ESOA
Company: DAKTruck Co
Address: 3020 Snow Rd Lansing MI 48917
Contact Phone ( ) 517 484 - 1905 Fax ( ) 517 - 322 - 2585
imail_emerrill@. Dktruck com



### Vendor Conflict of Interest Disclosure Form

All vendors interested in conducting business with the City of Ann Arbor must complete and return the Vendor Conflict of Interest Disclosure Form in order to be eligible to be awarded a contract. Please note that all vendors are subject to comply with the City of Ann Arbor's conflict of interest policies as stated within the certification section below.

If a vendor has a relationship with a City of Ann Arbor official or employee, an immediate family member of a City of Ann Arbor official or employee, the vendor shall disclose the information required below.

- No City official or employee or City employee's immediate family member has an ownership interest in vendor's company or is deriving personal financial gain from this contract.
- 2. No retired or separated City official or employee who has been retired or separated from the City for less than one (1) year has an ownership interest in vendor's Company.
- 3. No City employee is contemporaneously employed or prospectively to be employed with the vendor.
- 4. Vendor hereby declares it has not and will not provide gifts or hospitality of any dollar value or any other gratuities to any City employee or elected official to obtain or maintain a contract.
- 5. Please note any exceptions below:

Name of City of Ann Arbor employees, elected	( ) Relationship to employee
officials or immediate family members with whom there may be a potential conflict of interest.	( ) Interest in vendor's company ( ) Other (please describe in box below)
	( ) Other (piease describe in box below

conflicts of interest and they are detected by the City, vendor will be exempt from doing business with the City.

I certify that this Conflict of Interest I contents are true and correct to my k certify on behalf of the Vendor by my s	nowledge an	d belief and I have the authority to so
1 K truck co Vendor Name		717-484-1905 Vendor Phone Number
Signature of Vendor Authorized	2-8-17	Edward Merry 11
Representative	Date	Representative

Questions about this form? Contact Procurement Office City of Ann Arbor Phone: 734/794-6500, procurement@a2gov.org

#### **INVITATION TO BID**

City of Ann Arbor Guy C. Larcom Municipal Building Ann Arbor, Michigan 48107

Ladies and Gentlemen:

The undersigned, as Bidder, declares that this Bid is made in good faith, without fraud or collusion with any person or persons bidding on the same Contract; that this Bidder has carefully read and examined the bid documents, including City Nondiscrimination requirements, Vendor Conflict of Interest Form, Instructions to Bidders, Bid Forms, Purchase Order (or Agreement) Terms and Conditions, General Conditions, Detailed Specifications, and all Addenda, and understands them. The Bidder declares that it conducted a full investigation of the work proposed and is fully informed as to the nature of the work and the conditions relating to the work's performance.

The Bidder acknowledges that it has not received or relied upon any representations or warrants of any nature whatsoever from the City of Ann Arbor, its agents or employees, and that this Bid is based solely upon the Bidder's own independent business judgment.

The undersigned proposes to perform all work described in the bid documents, including any addenda issued, and to furnish all necessary machinery, tools, apparatus, to do all the work, furnish all the materials, and complete the work in strict accordance with all terms of the Contract of which this Bid is one part.

In accordance with these bid documents, and Addenda numbered \_\_\_\_\_\_, the undersigned, as Bidder, proposes to perform at the sites in and/or around Ann Arbor, Michigan, all the work included herein for the amounts set forth in the Bid Forms.

Bidder further agrees that the cited provisions of Chapter 14 and Chapter 23 form a part of this Contract. The Bidder declares that it has become familiar with the City Conflict of Interest Disclosure Form and certifies that the statement contained therein is true and correct.

In submitting this Bid, it is understood that the right is reserved by the City to accept any Bid, to reject any or all Bids, to waive irregularities and/or informalities in any Bid, and to make the award in any manner the City believes to be in its best interest.

(This Space Intentionally Left Blank)

SIGNED THIS //	DAY OF
EDYKTruck Co Bidder's Name	Authorized Signature of Bidder
3020 Snow Rd Official Address	(Print Name of Signer Above)
517-749-2799	emerrill@Dktruck.com

#### **GENERAL CONDITIONS**

#### PROJECT SUMMARY

The City of Ann Arbor is looking for a single vendor to provide the specified chassis, body and related equipment for the fabrication of a tandem axle dump truck equipped with a Prentice knuckle boom loader to be used in the City's Forestry operations.

#### SINGLE VENDOR

The City of Ann Arbor will contract and deal with only a single vendor for this project. The single vendor will be responsible for all coordination between chassis, body and equipment manufacturers/suppliers.

#### BASIS OF DESIGN/ USE OF SPECIFIC PARTS OR EQUIPMENT

The City of Ann Arbor has noted manufacturer and model information throughout the detailed specifications as "basis of design." These manufacturer's and models are acceptable to the City or the vendor can provide an equivalent or better product. The City of Ann Arbor shall be the sole decision maker on an "equivalent" product. The City has noted "No substitutions" on certain products or components throughout the detailed specifications. As the City is standardizing certain components in our Fleet, a manufacturer or model noted as "No substitution" must be provided as specified.

#### **DELIVERY**

Equipment is to be delivered, with the cost included in the base bid, to the City of Ann Arbor Wheeler Service Center, Fleet Garage, located at 4251 Stone School Road, Ann Arbor, MI.

#### **DOWN PAYMENTS**

Any bid proposal submitted which requires a down payment or prepayment of any kind prior to delivery and acceptance of the item, as being in conformance with the specifications will not be considered for award.

#### **MANUALS**

Successful vendor to provide one complete set of service, parts, operations and maintenance manuals. Wiring schematics, service manuals and operator's manuals shall be supplied in printed form. Parts manuals will be acceptable on CD.

## DETAILED SPECIFICATIONS TANDEM AXLE CHASSIS

### **QUANTITY:**

One (1) New Tande	n Axle Chassis fo	or Public Works	<ul> <li>Forestry</li> </ul>	Operations.
-------------------	-------------------	-----------------	------------------------------	-------------

Offe (1) New Tarident Axie Chassis for Fubilic Works - Forestry Operations.				
MANUFACTURER/ MODEL/ MODEL YEAR OF CHASSIS:				
Manufacturer Western Star				
Model 4700 Model Year of Chassis 2018				
GROSS VEHICLE WEIGHT RATING:				
Gross vehicle weight rating to be a minimum 66,000 pounds.  Meets specification? YesNo				
CAB:				
Conventional style cab with tilt-type hood and fender assembly. Cab suspension to be air ride. Adjustable steering column including both tilt and telescoping features. Suspended brake and accelerator pedals. Heated west coast type 102", "breakaway style", door mounted mirrors with heated convex mirrors LH and RH. RH down view mirror. RH 8 inch stainless steel fender mounted convex mirror with tripod brackets. All mirrors and brackets to be stainless steel. One roof mounted air horn with shield and single electric horn. Power windows and door locks. Air conditioning with cab air filtration system. Ball shutoff valves for heater supply lines. Snow shield for fresh air intake. Stationary grille with non-removable bug screen mounted behind grille. Front fender extensions to minimize road spray. Exterior and interior grab handles mounted RH and LH. All glass tinted. Windshield to be 2-piece with heated wiper blade park areas. Upgraded/premium cab insulation. LH and RH front pillar post mounted Unity X335 Series X LED 6" Spotlight (black).  Meets specification? Yes No				
CAB ACCESSORIES:				
Door locks and ignition are to be keyed the same. Four (4) keys are to be supplied per truck. Supply an overhead storage console with fused 20-amp power cable wiring package for City's installation of 2-way radio. Center storage mounted on back wall. Wing style dash. 12-volt power supply in dash. Two (2) cup holders. Dual interior sun visors. AM/FM/WB radio with auxiliary input and four (4) speakers. Wet arm wipers with intermittent feature. Seat belts are to be orange in color.  Meets specification? Yes No				

## **SEATING:**

suspension and include three	(3) chamber air lumbar. Se	Driver and passenger seats to be air eat cushion to have extension feature Modura cloth. Both seats to have arm
1000.	Meets speci	fication? YesNo
PAINT:		
Cab color to Dupont Imron to be powder white.		58EA. Chassis to be black. Wheels fication? Yes No
ENGINE:		
	, 1250 ft/lb of torque @ 1,40 2014 Onboard Diagnostics/2 2008 CARB -Clean Idle	
minus 34 degrees. Minimum 1 protection system. Horton on/indicator light. Delco 12v 39M switch. Full flow oil filter. Eng	8.7 CFM air compressor. E off fan clutch with automati T HD/OCP starter with therr ine mounted fuel/water sep Coolant filter. Program eng with Donaldson air cleaner,	
	Meets speci	fication? YesNo
EXHAUST:		
treatment system. To include	automatic over the road reg outlet to be curved stack. St	senger side cab entry steps after eneration and a dash mounted ainless steel shield. Chassis must
	Meets speci	fication? Yes No
TRANSMISSION:		
speed signal. Dash mounted el system. Synthetic transmission coverage. Transmission oil che	provision. Firewall mounted ectronic push button shift cor fluid meeting Allison specific eck and fill with electronic oil	(No substitution) customer access connector to provide ntrol. Allison transmission Prognostics ation requirement for extended warranty level check. Frame mounted water to brake engaged is to be supplied.
	Meets specif	ication? YesNo

### **AXLES:**

To include-
TRW THP-60 power steering with RCH45 auxiliary gear. Four-quart power steering reservoir. Oil/air power steering cooler. Oil seals with vented front hubcaps with window, center, and side oil plugs. Synthetic axle lube.
Rear Axle: Meritor RT-46-164 R-Series 46,000 lb. capacity. To include-
Meritor MXL 176T extended tube driveline with half round yokes. Meritor MXL 17T extended lube interaxle driveline with half round yokes. Oil seals. Driver controlled traction differential for both axles with dash-mounted switch (to lock all 8 drive wheels). Synthetic axle lube. Ratio to be
5.38:1. Meets specification? YesNo
SUSPENSION:
Front Suspension: 20,000 lb. capacity flat leaf spring suspension.  To include-
Graphite bronze bushings with seals. Front shocks.
Rear Suspension: Hendrickson Haulmaax HMX 460 46,000 lb. suspension (No substitution) To include-
Axle spacing at 52 inches. Shock absorbers on both axles.  Meets specification? Yes No
FRAME:
Single channel steel rails with an integral 24-inch front frame extension. Partial frame reinforcement at front suspension. Huck bolt fasteners. Dimension: $\frac{1}{2}$ " x 3.64" x 11-7/8" RBM: 3,204,000 SM: 26.70 PSI: 120,000 - 444.9 With Selected options
Chassis frame height not to exceed 40" to facilitate legal height limits after mounting of knuckle boom loader.
Meets specification? Yes No
BRAKE SYSTEM:
Air brake system with WABCO 4S/4M ABS system. Wabco SS-1200 Plus air dryer with integral air governor and heater. Automatic heated moisture drains on all air tanks. Brake dust shields on all axles. Haldex automatic slack adjusters on all axles. Rear parking chambers are to be Haldex Goldseal longstroke chambers (No Substitution) Cast iron brake drums. Rear axle
brake chambers to be indexed so as not to interfere with asphalt paving.
Front Brakes: Meritor 16.5 x 6 Q+ cam.  Rear Brakes: Meritor 16.5 x 7 Q+ cam.
Rear Brakes: Meritor 16.5 x 7 Q+ cam.  Meets specification? Yes No  Bendix Eversure chambers
Bendix Eversure Chambers

FUEL TANK/ DEF TANK:			
Fuel tank to be a left side step tank. Six gallon DEF tank is to be full at delivery.	DEF tank mounted LH Meets specification?		
TIRES/ WHEELS:			
Front Tires: Michelin XZY-3 385/65R22.5 18 Rear Tires: Michelin XDE M/S 11R22.5H 1			
Front Wheels: Accuride 29807 22.5X12.25 Rear Wheels: Accuride 28828 22.5X8.25 10-Hull			l Disc.
	Meets specification?	Yes	No
ELECTRICAL:			
12V negative ground electrical system with some for battery cables with additional frame ground remote battery volt sense. Three (3) group threaded stud batteries. Positive load batted Vehicle interface wiring with body builder conaccessory rocker switches pre-wired and furby the body company.	freturn. Delco Remy 16 31, 12-volt maintenance ry disconnect switch mo nnector mounted back o	0 amp 28-SI ali e free 3375 co ounted in-cab of cab. Six OEN	ternator with mbined CCA on driver's side. Il installed
by the body company.	Meets specification?	Yes	No
CHASSIS LIGHTING:			
Halogen headlights. Interior dome light with L as necessary to transit vehicle to body outfit			. •
GAUGES/ INSTRUMENTS:			
Washer fluid level indicator. Primary and swarning light and buzzer. Air restriction indicodometer, trip, hourmeter, diagnostics, and verified coolant gauge. Transmission oil tem Speedometer. Tachometer. Self-cancelling	cator dash mounted. Ce roltage. Fuel gauge. Fr perature gauge. Engine	enter display to uel filter restric e oil pressure (	include tion indicator. gauge.
CHASSIS WARRANTY:	·		
Chassis: One (1) Year / Unlimited Miles Engine, Emissions and Aftertreatment: Five Transmission: Five (5) Years / Unlimited Towing: Two (2) Years / Unlimited Miles		. /	tible
	MICHES SOCIUCADON	T 114 \ /	INIC)

#### **CHASSIS MISCELLANEOUS:**

- Completed truck to have a 5 lb. dry-type Rechargeable ABC fire extinguisher with brass or stainless steel valve, 3 triangular reflectors and comply with all applicable National Highway Transportation Safety Administration Standards.
- The successful bidder must provide three (3) years of online parts and service access.
- The successful bidder must provide a list of serial and model numbers for chassis components (engine, transmission, axle, etc.).
- Successful bidder shall supply warranty terms and time/mileage limits of complete unit(s) based on posted in service date.

 a(c) bases on process					
	Meets specification?	Yes_	1/	No_	

# DETAILED SPECIFICATIONS DUMP BODY and PRENTICE KNUCKLE BOOM LOADER (FOR TANDEM AXLE)

#### **QUANTITY:**

One (1) New dump body and Prentice Knuckle Boom Loader for Public Works, Forestry Operations.

<b>JERA</b>	

Galian 400U

- The basis of design is a Warren U650 dump body 12' long X X'8" wide
- Inside height 30" Taper to 12" last 30" of the body.
- · Front bulkhead height 48".
- · Tailgate height 12".
- · Boxed top rail with dirt shedding design.
- 45 degree sloped dirt shedding rub rails. Front bulkhead to have three (3) 3" @ 5
   lbs. per ft. structural channel full horizontal braces and two (2) vertical braces/stiffeners.
- · Side braces, 6 per side.
- · Front post, 1 per side.
- Corner post, lower rubrail and top rail to be ASTM A570 hl-tensile steel.
- 4"x4" x 1/8" boxed tube rubrail.
- Longsills, 6" I-beam @ 12.50 lbs. per ft.
- Crosssills 4" channel @ 5.4 lbs. per ft. on 12" centers.
- Full depth front and rear pillar corner posts.
- 3/16" AR450 steel construction of sides. ¼ " AR 450 steel floor, front and tailgate.
   Continuously welded 100% throughout.
- 9" > floor to sides radius.
  - Tailgate latch air operated, with center D-ring lift loop. Tailgate to be heavy duty.
     Tailgate to have a 30"W x 12"H x 3/8" protective plate welded on tailgate for protection when stowing the grapple.
  - Body prop klt on each side of the frame.
  - ¼ cab shield for tarp assembly to set on.
  - Install mud flaps in front of and behind the drive tires. Rear mud flaps to be mounted from chains.
  - 36"H x 40"W Steel storage box with structural channel iron interior frame, full width to set between the prentice log loader and the front of the dump body. Full end doors each side with paddle latches. 1/4" x 4" steel lip around top of box with drain holes in the corners.
  - Heavy duty Grapple rest at rear of body, constructed of 4" ship and car channel to extend into the longsills 3'.
  - Rear dump body apron below tailgate shall have two (2) series 60 oval cutouts on each side for Stop/Turn/Tail lights and amber warning lights with protection guards over the holes so lights are not damaged when dumping material.

weeks specification? Tes NO	Meets specification?	Yes	1/	No	
-----------------------------	----------------------	-----	----	----	--

HO	ST.
110	<u>y.,</u>
	Greasable rear hinge and replaceable rear pin
ELE	CTRIC TARP SYSTEM:
•	Aluminum tarp arms.  3-spring tarp arms with offset elbow kit. Tarp system shall be mounted so that when the tarp is in the rolled up position the bows do not extend into the loading area of the dump box.  Mesh tarp cover.
	Meets specification? Yes No
ELEC	CTRICAL AND LIGHTING:
	Two (2) SoundOff Predator2 LED lights on cab shield, one each, side-facing, at top of dump. With front facing shields to prevent blinding of the driver.  Two (2) SoundOff Predator2 LED amber lights mounted in chassis grille. Switched seperatley from the other warning lights.  Two (2) SoundOff Predator2 LED work lights mounted on rear body corners.  Two (2) SoundOff Predator2 LED work lights mounted on rear body corners.  Two (2) SoundOff series 60 oval amber LED strobe warning lights mounted in grommets in rear of dump body apron below the tailgate with upper spill deflectors/protectors. Wired to flash an alternating pattern.  Betts junction box mounted at the rear of the dump body.  Proximity switch for body-up light. Omron Model TL-W20ME2.  Wire cab marker light to electrical disconnect switch.  Back-up alarm. Ecco Model 510.  All wiring connections to be soldered and heat shrunk. All wiring to be in protective loom.  Wire rear amber warning lights to also come on when transmission is shifted into reverse.  Wire and install City of Ann Arbor supplied GPS/AVL system.  Inside cab, operators heads up warning lamps for outriggers down, dump body up, low hydraulic oil level and tailgate open, clearly marked  Body lighting to meet FMVSS 108  All body lighting to meet FMVSS 108  All body lighting to be LED  Install Whelen Model L21HAP LED amber strobe lights to upper brackets of both LH and RH west coast mirrors, with weatherpack connectors.  Auxiliary switches to include, PTO, air tailgate, tarp, amber grill warning lights, all other amber warning lights, LED work lights.
	Meets specification? Yes V No

## **DUMP BODY MISCELLANEOUS:**

- · Install Cable markers on both ends of the bumper.
- Paint: dump body, body hinge, body props, hoist and attaching hardware shall be painted black.
- Install a 12" structural C-channel front bumper with tapered ends, painted black.
- Driver's side shall provide a three step egress to cab.
- Two front tow hooks
- Wilton Model 10025 5" ATV Vise mounted curbside on front bumper
- One (1) 24" x 1" Traffic cone storage, mounted streetside front bumper
- ¾" rear hitch plate (no hitch).
- Parts manual shall be supplied for dump body and hoist.

Meets specification? Yes\_

\_\_ No \_\_\_

#### LOG LOADER

- Prentice Model 2124 Knuckle boom loader (no substitutions)
- Behind cab mount design.
- Knuckle boom shall have minimum reach of 22'.
- Shall have a 3' hydraulic extension for a full reach of 25'.
- Outriggers shall span a minimum of 10° 10" or as wide as necessary to prevent truck from tipping under ALL operating conditions.
- Telescopic A-frame stabilizers with individual platform controls for uneven terrain.
- Outriggers shall be equipped with 10" x 15" steel pads and a set of 24" x 24" poly pads with carrying handles.
- Boom storage/travel height shall be approximately 13' and not to exceed 13'4".
- Knuckle boom continuous rotation shall be powered by a low speed high torque hydraulic motor that drives the turntable through a ring and pinion type spur gear train.
- Unit shall have a seat control with split flow control system necessitating a tandem hydraulic pump configuration, 21GPM and 19GPM minimum.
- Hydraulic pump shall be an electric shift, PTO gear type having a minimum flow rate of 40 gallons per minute at 3,500 PSI.
- Hydraulic oil reservoir shall have a minimum capacity of 65 gallons and be suitable for use as a central reservoir for the dump body, log loader and winch hydraulic pumps.
- Reservoir shall be equipped with a filler breather cap, properly sized suction strainers, 10
  micron return line filters with filter condition indicator. Shall also include oil level
  sight/temperature gauge, clean out cover, relief valve and full flow ball valves in the suction
  lines.
- Hydraulic system, split flow tandem circuit hydraulic system. Stack sections with mechanical
  joysticks type control valve with port reliefs and anti-cavitation valves for loader protection
  and control. Operation handles, pump control valve outrigger controls at the base of the
  boom controls located at the operators seat.
- Diagnostic quick coupler nipples located at control valve for all hydraulic functions.
- Two return spin on filters, 2 nominal/10 absolute micron filter, 25 micron case drain filter,
- Direct mount PTO drive, bi-rotational.
- "A" Frame pedestal design formed high strength steel plate.
- Knuckle boom shall be equipped with a Rotobec Model 040 pulpwood grapple (no substitutions) and shall have three (3) Case shank (tooth holder) Pt. No. D48212 welded on to the leading edge of the grapple. The opposing side of the grapple shall have two (2) shanks welded on evenly spaced between the opposing shanks for a total of five (5). Five (5) Case Points Pt. No. CD-39093 (teeth) shall be installed on the shanks for use in digging.

- Grapple shall be capable of continuous rotation via a hydraulic rotator with integral hydraulic swivel. Rotobec Model RT-222-2 (no substitutions).
- Grapple lined with ¼" AR450 steel plate.
- Fixed platform 86" x 42" over cab (heavy-duty expanded metal).
- Holding valves on all hydraulic cylinders.
- Lifting capacity @ maximum reach to be 3,500 lbs. minimum.
- · Access ladder to operator station shall be on the street side.
- LED work lights on stick boom and operators station platform with protective guards wired through the swivel collector ring.
- Parts and service manuals shall be supplied for the log loader, grapple and swivel.


weets specification? Yes V No	Meets specification?	Yes		No	
-------------------------------	----------------------	-----	--	----	--

#### WINCH

- Ramsey Model HX600R 12,000 lb. hydraulic winch (basis of design).
- Hydraulic winch to be mounted on the front of the truck between the frame rails.
- Winch shall not interfere with tilt hood operations.
- Winch shall be powered by a Char-Lynn or equal hydraulic motor, powered by the vehicles central hydraulic system. Unit shall be controlled by a forward/reverse hydraulic control valve. Hydraulic control valve shall be mounted on the front bumper with a single lever control and a single lever air operated control in the cab mounted on a fabricated tower.
- · Joystick control to be clearly marked, winch in/out,
- · Winch shall have a heavy-duty roller fairlead.
- Drum shall be of sufficient size to hold 200' of ½" wire rope with a minimum breaking strength of 26,600 lbs.
- Winch cable shall have a ½" alloy Shur-Loc swivel hook.
- Parts manual shall be supplied for winch.

Meets specification?	Yes	$\underline{V}$	No	

Please list any deviation from these specifications on a separate page. Any deviation must include a detailed explanation of the difference with the specifications.



Ph: (586) 991-0054 Fx: (586) 991-0074

Quote No. J31131

STATE REG NO: F151568 DEALER LICENSE NUMBER: B6542 Page 1

Customer: 2216

D & K TRUCK COMPANY

3020 SNOW ROAD

LANSING MI 48917

05/17/17: Quote Date

: Expire Date

N30: Terms

: Delivery

Contact:

Phone: 734-994-2700

Fax: 734-994-8297

1) LOG LOADER PACKAGE ITB#4499 PER ATTACHED SPECIFICATIONS

PRICE AS SPECIFIED ABOVE W/ GALION DUMP AND

GALION (CLASS 60) HOIST.....\$ 106,358.00

OPTION:

FOR GALION BODY WITH WARREN U90-7724 HOIST (CLASS 90)

ADD .....\$3,762.00

\*\*\*NOTE: WARREN BODY WILL NOT BUILD THIS BODY AS SPECIFIED\*\*\*\*

THANK YOU,

JAMES A BROWN