

# PROJECT #SP19-019


## SITE PLAN FOR CITY COUNCIL APPROVAL

FOR

# MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION

PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES

PARCEL ID: 09-09-30-318-028  
 2151 WEST STADIUM BOULEVARD  
 CITY OF ANN ARBOR  
 WASHTENAW COUNTY, MICHIGAN



Know what's below  
 Call before you dig.

**APPLICANT**


MICHIGAN SCHOOLS AND GOVERNMENT CREDIT UNION  
 40400 GARFIELD ROAD  
 CLINTON, MICHIGAN 48038  
 (586)-263-8800

**OWNER**

WEST STADIUM, LLC  
 P.O. BOX 1325  
 ANN ARBOR, MICHIGAN 48106

**PETITIONER'S AGENT**

MICHAEL BLANEK  
 MBLANEK@STUCKYVITALE.COM  
 27172 WOODWARD AVENUE  
 ROYAL OAK, MICHIGAN 48067  
 (248)-546-6700



SOURCE: USGS ONLINE MAPS

**LOCATION MAP**


SCALE: 1" = 2,000'±



SOURCE: GOOGLE EARTH PRO

**AERIAL MAP**

SCALE: 1" = 200'±



SOURCE: CITY OF ANN ARBOR ZONING MAP

**ZONING MAP**

SCALE: 1" = 200'±

**PROJECT SUMMARY**

A 3,803 SQUARE FOOT ONE-STORY STANDALONE CREDIT UNION IS BEING PROPOSED ON SITE. A DRIVE-THRU IS PROPOSED ALONG THE REAR OF THE BUILDING IN ACCORDANCE WITH THE SPECIAL USE STANDARDS FOR DRIVE-THRU FACILITIES. THE SITE IS LOCATED WITHIN BOTH THE C3 - FRINGE COMMERCIAL DISTRICT & THE C2B - BUSINESS SERVICE DISTRICT. C3 ZONING HAS BEEN ASSUMED FOR ALL ZONING REQUIREMENTS. PARKING IS PROPOSED ON SITE ALONG WITH ASSOCIATED BICYCLE PARKING IN ACCORDANCE WITH THE CURRENT REQUIREMENTS AND STANDARDS. STORMWATER WILL BE DETAINED AND RELEASED TO THE EXISTING STORM SEWER WITHIN THE WEST STADIUM BOULEVARD RIGHT-OF-WAY. PREVIOUSLY, AN AUTO ZONE WAS APPROVED ON THE PROPERTY. A SPECIAL EXCEPTION USE PETITION (SEU19-003) IS REQUIRED AS PART OF THIS PLAN. A ZONING PETITION (Z19-010) IS REQUIRED TO ZONE THE PROPERTY AS C-3.

**STATEMENT OF INTEREST IN LAND**

DEVELOPER HAS ENTERED INTO A LAND CONTRACT WITH CURRENT PROPERTY OWNER. FINAL SALE OF PARCELS IS CONTINGENT ON SITE PLAN AND OTHER PROJECT APPROVALS.

**PARCEL AREA**

51,016± LEGAL SQUARE FEET = 1.171± ACRES

**LEGAL DESCRIPTION**

THE LAND SITUATED IN THE CITY OF ANN ARBOR, COUNTY OF WASHTENAW, STATE OF MICHIGAN, IS DESCRIBED AS FOLLOWS:

COMMENCING AT THE SOUTHWEST CORNER OF SECTION 30, TOWN 2 SOUTH, RANGE 6 EAST; THENCE NORTH 85.471 FEET; THENCE NORTH 75 DEGREES 48 MINUTES 00 SECONDS EAST 743.10 FEET; THENCE SOUTH 01 DEGREES 56 MINUTES 00 SECONDS EAST 451.29 FEET FOR A POINT OF BEGINNING; THENCE NORTH 65 DEGREES 10 MINUTES 00 SECONDS EAST 150.49 FEET; THENCE SOUTH 03 MINUTES 00 SECONDS WEST 11.02 FEET; THENCE NORTH 65 DEGREES 10 MINUTES 00 SECONDS EAST 173.96 FEET; THENCE SOUTH 24 DEGREES 50 MINUTES 00 SECONDS EAST 140.00 FEET; THENCE SOUTH 65 DEGREES 10 MINUTES 00 SECONDS WEST 383.29 FEET; THENCE NORTH 01 DEGREES 56 MINUTES 00 SECONDS WEST 162.97 FEET TO THE POINT OF BEGINNING.

PLANS PREPARED BY:




Detroit, MI · New York, NY  
 Princeton, NJ · Tampa, FL · Rutherford, NJ  
 www.stonefieldeng.com

607 Shelby Suite 200, Detroit, MI 48226  
 Phone 248.247.1115

**PLAN REFERENCE MATERIALS:**

- THIS PLAN SET REFERENCES THE FOLLOWING DOCUMENTS INCLUDING, BUT NOT LIMITED TO:
  - BOUNDARY / TOPOGRAPHIC SURVEY PREPARED BY KEM-TEC & ASSOCIATES DATED 12/13/2018; REVISED 08/02/2019
  - ARCHITECTURAL PLANS
  - GEOTECHNICAL REPORT
  - AERIAL MAP OBTAINED FROM GOOGLE EARTH PRO
  - PHASE-1 REPORT PREPARED BY PM ENVIRONMENTAL DATED 12/26/2018
- ALL REFERENCE MATERIAL LISTED ABOVE SHALL BE CONSIDERED A PART OF THIS PLAN SET AND ALL INFORMATION CONTAINED WITHIN THESE MATERIALS SHALL BE UTILIZED IN CONJUNCTION WITH THIS PLAN SET. THE CONTRACTOR IS RESPONSIBLE TO OBTAIN A COPY OF EACH REFERENCE AND REVIEW IT THOROUGHLY PRIOR TO THE START OF CONSTRUCTION.

**DRAWING SCALE**



**SHEET INDEX**

DRAWING TITLE	SHEET #
COVER SHEET	C-1
ALTA / TOPOGRAPHIC SURVEY	1
DEMOLITION PLAN	C-2
SITE PLAN	C-3
GRADING PLAN	C-4
STORMWATER MANAGEMENT PLAN	C-5 & C-6
UTILITY PLAN	C-7
LIGHTING PLAN	C-8
LANDSCAPING PLAN	C-9
SOIL EROSION & SEDIMENT CONTROL PLAN	C-10
CONSTRUCTION DETAILS	C-11 THRU C-14

**ARCHITECTURAL SHEETS**

DRAWING TITLE	SHEETS
ARCHITECTURAL FLOOR PLAN	A1.1
EXTERIOR ELEVATION	A3.1
EXTERIOR ELEVATION	A3.2
EXTERIOR RENDERING	A3.3

ISSUE	DATE	BY	DESCRIPTION
5	10-30-2019	KHL	REVISIONS PER 3RD PLANNING REVIEW COMMENTS
4	10-11-2019	KHL	REVISIONS PER 2ND PLANNING REVIEW COMMENTS
3	08-22-2019	ADG	REVISIONS PER PLANNING REVIEW COMMENTS
2	08-08-2019	ADG	REVISIONS PER PLANNING REVIEW COMMENTS
1	05-30-2019	ADG	SUBMISSION FOR SITE PLAN APPROVAL

NOT APPROVED FOR CONSTRUCTION


**STONEFIELD**  
 engineering & design

Detroit, MI · New York, NY  
 Princeton, NJ · Tampa, FL · Rutherford, NJ  
 www.stonefieldeng.com  
 607 Shelby Suite 200, Detroit, MI 48226  
 Phone 248.247.1115

SITE PLAN FOR CITY COUNCIL APPROVAL

MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION  
 PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES

PARCEL ID: 09-09-30-318-028  
 2151 WEST STADIUM BOULEVARD  
 CITY OF ANN ARBOR  
 WASHTENAW COUNTY, MICHIGAN



**STONEFIELD**  
 engineering & design


SCALE: AS SHOWN PROJECT ID: M-19060

CITY OF ANN ARBOR PROJECT NUMBER: SP19-019

TITLE: **COVER SHEET**

DRAWING:

**C-1**



**VICINITY MAP**  
(NOT TO SCALE)

**PARCEL AREA**  
51,016± SQUARE FEET = 1.171± ACRES


**BASIS OF BEARING**  
SOUTH 24°50'00" EAST, BEING THE WESTERLY RIGHT OF WAY LINE OF WEST STADIUM BOULEVARD, AS DESCRIBED.

**PARKING**  
NO MARKED PARKING ON SITE.

**BENCHMARK**  
**SITE BENCHMARK #1**  
SOUTHEAST CORNER OF CONCRETE STEP AT ENTRANCE OF QUALITY GROOMING, NORTH SIDE ON SUBJECT PROPERTY.  
ELEVATION = 937.60' (NAVD 88 DATUM)

**SITE BENCHMARK #2**  
ARROW OF HYDRANT IN FRONT OF SUBJECT PROPERTY ACROSS THE STREET IN THE NORTHERLY RIGHT OF WAY OF STADIUM BLVD.  
ELEVATION = 932.86' (NAVD 88 DATUM)


**SURVEYOR'S NOTE**  
THE UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND EXISTING DRAWINGS. THE SURVEYOR MAKES NO GUARANTEES THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED ALTHOUGH HE DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION AVAILABLE. THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES OTHER THAN THE STRUCTURE INVENTORY SHOWN HEREON.



**PROPERTY DESCRIPTION**  
THE LAND SITUATED IN THE CITY OF ANN ARBOR, COUNTY OF WASHTENAW, STATE OF MICHIGAN, IS DESCRIBED AS FOLLOWS:  
COMMENCING AT THE SOUTHWEST CORNER OF SECTION 30, TOWN 2 SOUTH, RANGE 6 EAST; THENCE NORTH 854.71 FEET; THENCE NORTH 75 DEGREES 48 MINUTES 00 SECONDS EAST 743.10 FEET; THENCE SOUTH 01 DEGREES 56 MINUTES 00 SECONDS EAST 451.29 FEET FOR A POINT OF BEGINNING; THENCE NORTH 65 DEGREES 10 MINUTES 00 SECONDS EAST 150.49 FEET; THENCE SOUTH 00 DEGREES 03 MINUTES 00 SECONDS WEST 11.02 FEET; THENCE NORTH 65 DEGREES 10 MINUTES 00 SECONDS EAST 173.96 FEET; THENCE SOUTH 24 DEGREES 50 MINUTES 00 SECONDS EAST 140.00 FEET; THENCE SOUTH 65 DEGREES 10 MINUTES 00 SECONDS WEST 383.29 FEET; THENCE NORTH 07 DEGREES 56 MINUTES 00 SECONDS WEST 162.97 FEET TO THE POINT OF BEGINNING.

**LEGEND**

●	SET 1/2" REBAR WITH CAP P.S. 47976
○	FOUND MONUMENT (AS NOTED)
○	FOUND SECTION CORNER (AS NOTED)
(R&M)	RECORD AND MEASURED DIMENSION
(R)	RECORD DIMENSION
(M)	MEASURED DIMENSION
○	GROUND ELEVATION
○	UTILITY POLE
○	GAS METER
○	GAS VALVE
○	CLEANOUT
○	SANITARY MANHOLE
○	SQUARE CATCH BASIN
○	STORM DRAIN MANHOLE
○	WATER GATE MANHOLE
○	FIRE HYDRANT
○	WATER VALVE
○	MONITOR WELL
○	LIGHT POLE WITH STREET LAMP
○	LIGHTPOST/LAMP POST
---	PARCEL BOUNDARY LINE
---	ADJOINER PARCEL LINE
---	EASEMENT (AS NOTED)
---	BUILDING
---	BUILDING OVERHANG
---	CONCRETE CURB
---	PARKING
---	EDGE OF CONCRETE (CONC.)
---	EDGE OF ASPHALT (ASPH.)
G	GAS LINE
S	SANITARY LINE
r	STORM LINE
w	WATER LINE
e	ELECTRIC LINE
~	TREE / BRUSH LINE (AS NOTED)
x	FENCE (AS NOTED)
---	WALL (AS NOTED)
---	OVERHEAD UTILITY LINE
---	MINOR CONTOUR LINE
---	MAJOR CONTOUR LINE
---	BUILDING HATCH
---	ASPHALT HATCH
---	CONCRETE HATCH



**TITLE REPORT NOTE**  
ONLY THOSE EXCEPTIONS CONTAINED WITHIN THE CHIRCO TITLE AGENCY, INC. COMMITMENT No. C-153263, DATED OCTOBER 26, 2018, AND RELISTED BELOW WERE CONSIDERED FOR THIS SURVEY. NO OTHER RECORDS RESEARCH WAS PERFORMED BY THE CERTIFYING SURVEYOR.

11. JOINT DRIVEWAY AGREEMENT AS RECORDED IN LIBER 889, PAGE 531, WASHTENAW COUNTY RECORDS. (AS SHOWN)

**SURVEYOR'S CERTIFICATION**  
TO MSCO, CHIRCO TITLE AGENCY, AND FIDELITY NATIONAL TITLE INSURANCE COMPANY:  
THIS IS TO CERTIFY THAT THIS MAP OR PLAT AND THE SURVEY ON WHICH IT IS BASED WERE MADE IN ACCORDANCE WITH THE 2016 MINIMUM STANDARD DETAIL REQUIREMENTS FOR ALTA/NSPS LAND TITLE SURVEYS, JOINTLY ESTABLISHED AND ADOPTED BY ALTA AND NSPS, AND INCLUDED ITEMS 2, 4, 7A, 8, AND 9 OF TABLE A, THEREOF. THE FIELD WORK WAS COMPLETED ON 12/13/18.

DATE OF PLAT OR MAP: 07/03/19  
**DRAFT**  
ANTHONY T. SYCKO, JR., P.S.  
PROFESSIONAL SURVEYOR  
MICHIGAN LICENSE NO. 47976  
22556 GRATIOT AVE., EASTPOINTE, MI 48021  
TSycko@kemttec-survey.com

**ALTA / NSPS LAND TITLE SURVEY**  
PREPARED FOR: STUCKY-VITALE ARCHITECTS  
2151-2161 W. STADIUM BLVD., ANN ARBOR MICHIGAN 48103,  
PART OF THE SOUTHWEST 1/4 OF SECTION 30,  
TOWN 2 SOUTH, RANGE 6 EAST

**KEM-TEC**  
PROFESSIONAL ENGINEERING, SURVEYING & ENVIRONMENTAL SERVICES  
A GROUP OF COMPANIES  
Grand Blanc  
Ann Arbor  
Eastpointe  
Detroit  
(810) 782.7222  
(734) 394.0888  
(734) 759.0767  
(419) 889.7248  
FAX: (810) 684.0001  
(734) 394.0888  
(734) 759.0767  
www.kemttec.com  
www.kemttec.companies.com

DRAWN BY:	DLD/MRU	DATE:	07/03/19
CHECKED BY:	ATS	DATE:	07/03/19
DATE:	JULY 03, 2019	SCALE:	1" = 20'
PROJECT NO.:	18-04300		

ALL EXISTING GRASSES / SHRUBS / BRUSH ON SITE TO BE REMOVED. CONTRACTOR TO HYDROSEED AREAS AS NECESSARY.

SITE CONTAINS CONTAMINATED SOILS. CONTRACTOR TO FOLLOW GUIDELINES CONTAINED WITHIN THE DUE CARE PLAN.

ALL FEATURES WITHIN THE RIGHT-OF-WAY ARE TO REMAIN UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IF SIGNIFICANT DISCREPANCIES ARE DISCERNED BETWEEN THIS PLAN AND FIELD CONDITIONS.

ALL SITE FEATURES WITHIN THE LIMIT OF DISTURBANCE INDICATED ON THIS PLAN ARE TO REMAIN AND BE PROTECTED THROUGHOUT CONSTRUCTION UNLESS OTHERWISE NOTED. THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IF SIGNIFICANT DISCREPANCIES ARE DISCERNED BETWEEN THIS PLAN AND FIELD CONDITIONS



SYMBOL	DESCRIPTION
---	FEATURE TO BE REMOVED / DEMOLISHED
— LOD —	LIMIT OF DISTURBANCE
- - -	SAW CUT LINE / LIMIT OF MILLING
[Pattern]	CONCRETE REMOVAL
⊙	TEST PIT



Know what's below  
Call before you dig.

**DEMOLITION NOTES**

1. THE WORK REFLECTED ON THE DEMOLITION PLAN IS TO PROVIDE GENERAL INFORMATION TOWARDS THE EXISTING ITEMS TO BE DEMOLISHED AND/OR REMOVED. THE CONTRACTOR IS RESPONSIBLE TO REVIEW THE ENTIRE PLAN SET AND ASSOCIATED REPORTS/REFERENCE DOCUMENTS INCLUDING ALL DEMOLITION ACTIVITIES AND INCIDENTAL TASKS NECESSARY TO COMPLETE THE SITE IMPROVEMENTS.
2. THE CONTRACTOR IS RESPONSIBLE TO DETERMINE THE MEANS AND METHODS OF DEMOLITION ACTIVITIES.
3. EXPLOSIVES SHALL NOT BE USED UNLESS WRITTEN CONSENT FROM BOTH THE OWNER AND ANY APPLICABLE GOVERNING AGENCY IS OBTAINED. BEFORE THE START OF ANY EXPLOSIVE PROGRAM, THE CONTRACTOR IS RESPONSIBLE TO OBTAIN ALL LOCAL, STATE, AND FEDERAL PERMITS. ADDITIONALLY, THE CONTRACTOR WILL BE RESPONSIBLE FOR ALL SEISMIC TESTING AS REQUIRED AND ANY DAMAGES AS THE RESULT OF SAID DEMOLITION PRACTICES.
4. ALL DEMOLITION ACTIVITIES SHALL BE PERFORMED IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL CODES. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING ALL UTILITIES ARE DISCONNECTED IN ACCORDANCE WITH THE UTILITY AUTHORITIES' REQUIREMENTS PRIOR TO STARTING THE DEMOLITION OF ANY STRUCTURE. ALL EXCAVATIONS ASSOCIATED WITH DEMOLISHED STRUCTURES OR REMOVED TANKS SHALL BE BACKFILLED WITH SUITABLE MATERIAL AND COMPACTED TO SUPPORT SITE AND BUILDING IMPROVEMENTS. A GEOTECHNICAL ENGINEER SHOULD BE PRESENT DURING BACKFILLING ACTIVITIES TO OBSERVE AND CERTIFY THAT BACKFILL MATERIAL WAS COMPACTED TO A SUITABLE CONDITION.
5. DEMOLISHED DEBRIS SHALL NOT BE BURIED ON SITE. ALL WASTE/DEBRIS GENERATED FROM DEMOLITION ACTIVITIES SHALL BE DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REQUIREMENTS. THE CONTRACTOR IS RESPONSIBLE TO MAINTAIN ALL RECORDS OF THE DISPOSAL TO DEMONSTRATE COMPLIANCE WITH THE ABOVE REGULATIONS.
6. THE CONTRACTOR IS TO CONFIRM ALL EXISTING UTILITY CROSSINGS PROVIDE A MINIMUM SEPARATION DISTANCE OF 18 INCHES. IF SEPARATION IS NOT PROVIDED, THE CONTRACTOR IS TO NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IN WRITING.
7. THE CONTRACTOR IS TO PERFORM A TEST PIT PRIOR TO CONSTRUCTION (RECORDED 30 DAYS PRIOR) AT LOCATIONS OF EXISTING UTILITY CROSSINGS FOR WATER AND SANITARY SEWER CONNECTION IMPROVEMENTS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IN WRITING.



ISSUE	DATE	BY	DESCRIPTION
5	10-30-2019	KHL	REVISIONS PER 3RD PLANNING REVIEW COMMENTS
4	10-11-2019	KHL	REVISIONS PER 2ND PLANNING REVIEW COMMENTS
3	08-22-2019	ADG	REVISIONS PER PLANNING REVIEW COMMENTS
2	08-08-2019	ADG	REVISIONS PER PLANNING REVIEW COMMENTS
1	05-30-2019	ADG	SUBMISSION FOR SITE PLAN APPROVAL

NOT APPROVED FOR CONSTRUCTION

**STONEFIELD**  
engineering & design

Detroit, MI • New York, NY  
Princeton, NJ • Tampa, FL • Rutherford, NJ  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

SITE PLAN FOR CITY COUNCIL APPROVAL

**MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION**

PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES

PARCEL ID: 09-09-30-3-18-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN



**STONEFIELD**  
engineering & design

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019

TITLE:  
**DEMOLITION PLAN**

DRAWING:  
**C-2**

V:\SP19\1906\STUCKY\WALFALE\2151 WEST STADIUM BOULEVARD, ANN ARBOR, MICHIGAN\LOT 028.DWG

### TABLE OF LAND USE AND ZONING

PARCEL ID: 09-09-30-318-028  
FRINGE COMMERCIAL DISTRICT (C3)

PROPOSED USE	EXISTING	PROPOSED	REQUIRED
CREDIT UNION	C3 / C2B	C3	C3
DRIVE-THRU FACILITIES			
ZONING REQUIREMENT			
MINIMUM LOT AREA	51,016 SF (1.17 AC)	51,016 SF (1.17 AC)	6,000 SF (0.14 AC)
MINIMUM LOT WIDTH	140.0 FT	140.0 FT	60 FT
MAXIMUM FLOOR AREA RATIO	N/A	7.5% (3,803 SF)	200%
MAXIMUM BUILDING HEIGHT	N/A	22.5 FT (1 STORY)	55 FT (4 STORIES)
MINIMUM FRONT YARD SETBACK	0.0 FT	10.0 FT	10 FT
MINIMUM SIDE YARD SETBACK (SOUTH)	0.0 FT	5.8 FT	0 FT
MINIMUM SIDE YARD SETBACK (NORTH)	0.0 FT	74.2 FT	0 FT
MINIMUM REAR YARD SETBACK	0.0 FT	209.5 FT	20 FT
PARKING - AUTOMOBILES (MINIMUM)	N/A	21 SPACES	18 SPACES MIN
PARKING - AUTOMOBILES (MAXIMUM)	N/A	21 SPACES	21 SPACES MAX
PARKING - BICYCLES	N/A	4 SPACES - CLASS C	2 SPACES - CLASS C

\* SEE DRIVE-THRU NOTE FOR ADDITIONAL INFORMATION

### OFF-STREET PARKING REQUIREMENTS

CODE SECTION	REQUIRED	PROPOSED
§ 5-19-1	CREDIT UNION MINIMUM: 1 SPACE PER 220 SF OF FLOOR AREA (3,803 SF) / (1,220 SF) = 18 SPACES CREDIT UNION MAXIMUM: 1 SPACE PER 180 SF OF FLOOR AREA (3,803 SF) / (1,180 SF) = 21 SPACES	21 SPACES
§ 5-19-2	90° PARKING SPACES: 9 FT X 18 FT WITH 22 FT DRIVE AISLE (3,803 SF) / (1,180 SF) = 21 SPACES	9 FT X 18 FT WITH 22 FT DRIVE AISLE
§ 5-19-1	BICYCLE PARKING: 1 SPACE PER 2,000 SF OF FLOOR AREA (3,803 SF) / (1,200 SF) = 2 SPACES	4 CLASS C SPACES

(\*) ONE-WAY DRIVE AISLE TO BE A MINIMUM 12 FT WIDE

### PROJECT INFORMATION AND ANALYSIS

**1. DEVELOPMENT PROGRAM:**  
A. DESCRIPTION: THE PROPOSED DEVELOPMENT IS LOCATED WITHIN BOTH THE C3 - FRINGE COMMERCIAL DISTRICT AND C2B - BUSINESS SERVICE DISTRICT. C3 ZONING HAS BEEN USED FOR ALL ZONING REQUIREMENTS. THE SITE IS CURRENTLY A VACANT LOT WITH 140 LINEAR FEET OF FRONTAGE ALONG WEST STADIUM BOULEVARD. PROPOSED ON SITE IS A 3,803 SQUARE FOOT CREDIT UNION WITH ASSOCIATED DRIVE-THRU FACILITIES. 21 PARKING SPACES ARE PROPOSED ON SITE WHERE 18 ARE REQUIRED. BICYCLE PARKING IS PROPOSED AS REQUIRED. A SINGLE CURB CUT IS BEING PROPOSED ALONG WEST STADIUM BOULEVARD. THIS PLAN REQUIRES NO VARIANCE AS DESIGNED THIS SITE CONTAINS CONTAMINATED SOILS WHICH WILL NOT ALLOW FOR INFILTRATION OF STORMWATER RUNOFF. STORMWATER WILL BE DETAINED AND ROUTED TO THE STORMWATER PIPE THAT RUNS ALONG WEST STADIUM BOULEVARD.  
B. CONSTRUCTION PHASING AND CONSTRUCTION COSTS:  
CONSTRUCTION WILL BE COMPLETED IN ONE PHASE BEGINNING IN APRIL OF 2020. CONSTRUCTION COST HAS NOT BEEN DETERMINED.  
ESTIMATED CONSTRUCTION COST: \$1,000,000

**2. COMMUNITY ANALYSIS:**  
A. IMPACT ON PUBLIC SCHOOLS:  
THE PROPOSED DEVELOPMENT WILL NOT HAVE A SIGNIFICANT IMPACT ON ANY SURROUNDING PUBLIC SCHOOLS.

**B. RELATIONSHIP OF INTENDED USE TO NEIGHBORING USES:**  
THIS DEVELOPMENT WILL FIT IN WITH THE CURRENT STYLE OF DESIGN ALONG WEST STADIUM BOULEVARD WHERE MANY BANKS AND FINANCIAL INSTITUTIONS ARE PRESENT.  
C. IMPACT OF ADJACENT USES ON PROPOSED DEVELOPMENT:  
PATRONS AT SURROUNDING DEVELOPMENTS MAY USE THE PROPOSED CREDIT UNION AND ASSOCIATED ATM FOR FINANCIAL SERVICES.  
D. IMPACT ON AIR, WATER QUALITY, AND EXISTING NATURAL FEATURES:  
THERE WILL BE NO SIGNIFICANT IMPACT ON THE AIR OR WATER QUALITY DUE TO THE DEVELOPMENT OF THIS SITE. THERE ARE NO LANDMARK TREES OR NATURAL FEATURES THAT ARE BEING DISTURBED ON SITE.  
E. IMPACT ON HISTORIC SITES OR STRUCTURES:  
THERE ARE NO HISTORIC SITES OR STRUCTURES LOCATED WITHIN THE PROPOSED SCOPE OF THE DEVELOPMENT.  
F. NATURAL FEATURES GENERAL DESCRIPTIONS AND IMPACTS:  
NO NATURAL FEATURES PRESENT ON SITE

**3. PUBLIC SIDEWALK MAINTENANCE STATEMENT:**  
ALL PUBLIC SIDEWALKS LOCATED WITHIN THE LIMIT OF DISTURBANCE SHOWN ARE TO BE PROTECTED AND REMAIN OPEN UNLESS OTHERWISE NOTED. CONTRACTOR IS TO ENSURE THAT SIDEWALKS ARE SAFE FOR USE BY PATRONS.

### TRAFFIC IMPACT ANALYSIS

Institute of Transportation Engineers (ITE) Trip Generation Manual, 10th Edition  
2151 W. Stadium Blvd.  
10/10/2019

Proposed Drive-Thru Credit Union  
Drive-In Bank - Land Use 912

3,803 SF	AM Peak Street Hour		PM Peak Street Hour	
	Enter	Exit	Enter	Exit
	21	15	39	39

Existing Restaurant  
High Turnover (Sit-Down) Restaurant - Land Use 932

4,300 SF	AM Peak Street Hour		PM Peak Street Hour	
	Enter	Exit	Enter	Exit
	24	19	26	16

Existing Gas Station  
Gasoline/Service Station - Land Use 944

4 Pumps	AM Peak Street Hour		PM Peak Street Hour	
	Enter	Exit	Enter	Exit
	21	20	26	28

\*Description for Land Use 944 "Gasoline/Service Station" indicates that "A gasoline/service station may also have ancillary facilities for servicing and repairing motor vehicles and may have a car wash." As such, trip generation associated with the previous car wash use were included within the gasoline/service station component of the site.


Total Trips	AM Peak Street Hour		PM Peak Street Hour	
	Enter	Exit	Enter	Exit
	45	39	54	44
Proposed	21	15	39	39

### SYMBOL DESCRIPTION

	PROPERTY LINE
	SETBACK LINE
	SAWCUT LINE
	PROPOSED CURB & GUTTER
	PROPOSED FLUSH CURB
	PROPOSED SIGNS / BOLLARDS
	PROPOSED BUILDING
	PROPOSED ASPHALT PAVEMENT
	PROPOSED CONCRETE
	PROPOSED STAMPED CONCRETE
	PROPOSED AREA LIGHT
	PROPOSED BUILDING DOORS

#### DRIVE-THRU NOTE

1. THE DRIVE-THROUGH FACILITIES MAY NOT BE LOCATED BETWEEN A STREET AND THE PRINCIPAL BUILDING, AND THE VEHICULAR CIRCULATION TO ENTER AND EXIT THE FACILITY MAY NOT IMPAIR THE GENERAL VEHICULAR CIRCULATION ON THE SITE OR THE PEDESTRIAN CIRCULATION ON AND OFF THE SITE.



#### GENERAL NOTES

- THE CONTRACTOR SHALL VERIFY AND FAMILIARIZE THEMSELVES WITH THE EXISTING SITE CONDITIONS AND THE PROPOSED SCOPE OF WORK (INCLUDING DIMENSIONS, LAYOUT, ETC.) PRIOR TO INITIATING THE IMPROVEMENTS IDENTIFIED WITHIN THESE DOCUMENTS. SHOULD ANY DISCREPANCY BE FOUND BETWEEN THE EXISTING SITE CONDITIONS AND THE PROPOSED WORK, THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC PRIOR TO THE START OF CONSTRUCTION. THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND ENSURE THAT ALL REQUIRED APPROVALS HAVE BEEN OBTAINED PRIOR TO THE START OF CONSTRUCTION. COPIES OF ALL REQUIRED PERMITS AND APPROVALS SHALL BE KEPT ON SITE AT ALL TIMES DURING CONSTRUCTION.
- ALL CONTRACTORS WILL TO THE FULLEST EXTENT PERMITTED BY LAW, INDEMNIFY AND HOLD HARMLESS STONEFIELD ENGINEERING & DESIGN, LLC, AND ITS SUB-CONSULTANTS FROM AND AGAINST ANY DAMAGES AND LIABILITIES INCLUDING ATTORNEYS FEES ARISING OUT OF CLAIMS BY EMPLOYEES OF THE CONTRACTOR IN ADDITION TO CLAIMS CONNECTED TO THE PROJECT AS A RESULT OF NOT CARRYING THE PROPER INSURANCE FOR WORKERS COMPENSATION, LIABILITY INSURANCE, AND LIMITS OF COMMERCIAL GENERAL LIABILITY INSURANCE.
- THE CONTRACTOR SHALL NOT DEVIATE FROM THE PROPOSED IMPROVEMENTS IDENTIFIED WITHIN THIS PLAN SET UNLESS APPROVAL IS PROVIDED IN WRITING BY STONEFIELD ENGINEERING & DESIGN, LLC.
- THE CONTRACTOR IS RESPONSIBLE TO DETERMINE THE MEANS AND METHODS OF CONSTRUCTION.
- THE CONTRACTOR SHALL NOT PERFORM ANY WORK OR CAUSE DISTURBANCE ON A PRIVATE PROPERTY NOT CONTROLLED BY THE PERSON OR ENTITY WHO HAS AUTHORIZED THE WORK WITHOUT PRIOR WRITTEN CONSENT FROM THE OWNER OF THE PRIVATE PROPERTY.
- THE CONTRACTOR IS RESPONSIBLE TO RESTORE ANY DAMAGED OR UNDERMINED STRUCTURE OR SITE FEATURE THAT IS IDENTIFIED TO REMAIN ON THE PLAN SET. ALL REPAIRS SHALL USE NEW MATERIALS TO RESTORE THE FEATURE TO ITS EXISTING CONDITION AT THE CONTRACTORS EXPENSE.
- CONTRACTOR IS RESPONSIBLE TO PROVIDE THE APPROPRIATE SHOP DRAWINGS, PRODUCT DATA, AND OTHER REQUIRED SUBMITTALS FOR REVIEW. STONEFIELD ENGINEERING & DESIGN, LLC WILL REVIEW THE SUBMITTALS IN ACCORDANCE WITH THE DESIGN INTENT AS REFLECTED WITHIN THE PLAN SET.
- THE CONTRACTOR IS RESPONSIBLE FOR TRAFFIC CONTROL IN ACCORDANCE WITH MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, LATEST EDITION.
- THE CONTRACTOR IS REQUIRED TO PERFORM ALL WORK IN THE PUBLIC RIGHT-OF-WAY IN ACCORDANCE WITH THE APPROPRIATE GOVERNING AUTHORITY AND SHALL BE RESPONSIBLE FOR THE PROCUREMENT OF STREET OPENING PERMITS.
- THE CONTRACTOR IS REQUIRED TO RETAIN AN OSHA CERTIFIED SAFETY INSPECTOR TO BE PRESENT ON SITE AT ALL TIMES DURING CONSTRUCTION & DEMOLITION ACTIVITIES.
- SHOULD AN EMPLOYEE OF STONEFIELD ENGINEERING & DESIGN, LLC BE PRESENT ON SITE AT ANY TIME DURING CONSTRUCTION, IT DOES NOT RELIEVE THE CONTRACTOR OF ANY OF THE RESPONSIBILITIES AND REQUIREMENTS LISTED IN THE NOTES WITHIN THIS PLAN SET.

#### FIRE DEPARTMENT NOTES:

- STORAGE AREA FOR CONSTRUCTION MATERIALS SHALL NOT INTERFERE WITH FIRE / EMERGENCY SITE ACCESS.
- FIRE HYDRANTS SHALL BE IN SERVICE DURING CONSTRUCTION

**ALL SIDEWALKS SHALL BE KEPT AND MAINTAINED IN GOOD REPAIR BY THE OWNER OF THE LAND ADJACENT TO AND ABUTTING THE SAME. PRIOR TO THE ISSUANCE OF THE FINAL CERTIFICATE OF OCCUPANCY FOR THIS SITE, ALL EXISTING SIDEWALKS IN NEED OF REPAIR MUST BE REPAIRED IN ACCORDANCE WITH CITY STANDARDS.**

**STONEFIELD**  
engineering & design

Detroit, MI - New York, NY  
Princeton, NJ - Tampa, FL - Rutherford, NJ  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

---

**NOT APPROVED FOR CONSTRUCTION**

**STONEFIELD**  
engineering & design

Detroit, MI - New York, NY  
Princeton, NJ - Tampa, FL - Rutherford, NJ  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

---

**SITE PLAN FOR CITY COUNCIL APPROVAL**

**MICHIGAN SCHOOLS & GOVERNMENT  
CREDIT UNION  
WITH DRIVE-THRU FACILITIES**

PARCEL ID: 09-09-30-318-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN


**STONEFIELD**  
engineering & design

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019  
TITLE: **SITE PLAN**  
DRAWING: **C-3**



# STORM WATER NARRATIVE

A 3,803 SQUARE FOOT ONE-STORY STANDALONE CREDIT UNION IS BEING PROPOSED ON SITE. A DRIVE-THRU IS PROPOSED ALONG THE REAR OF THE BUILDING IN ACCORDANCE WITH THE SPECIAL USE STANDARDS FOR DRIVE-THRU FACILITIES. THE SITE STORMWATER WILL BE TREATED VIA A MECHANICAL TREATMENT UNIT, DETAINED WITHIN AN ABOVE GROUND BASIN AND OUTLET TO THE WEST STADIUM BOULEVARD STORMWATER SEWER. THE PROPOSED MEASURES WILL MEET ALL WASHTENAW COUNTY WATER RESOURCES COMMISSION REQUIREMENTS. THE REAR OF THE SITE WHERE THE PROPOSED ABOVE GROUND BASIN IS LOCATED CONTAINS CONTAMINATED SOILS. TO MAKE SURE THERE ARE NO PATHWAYS FOR CONTAMINATION TO GET INTO THE STORM SYSTEM, THE PROPOSED BASIN WILL HAVE A THERMOPLASTIC LINER. THE RECOMMENDED CONFIGURATION FOR THE LINER WOULD CONSIST OF A 30 MIL POLYVINYL CHLORIDE (PVC) WITH 8 OUNCE NON-WOVEN GEOTEXTILE UNDERLAYMENT AND OVERLAYMENT. PVC IS AN EFFECTIVE LINER MATERIAL AS IT OFFERS GREAT CHEMICAL RESISTANCE TO AREAS WITH HIGH CONTAMINANT CONCENTRATIONS. PROVIDES FLEXIBILITY AND VERSATILITY, AND CAN BE INSTALLED AND MAINTAINED BY A CONTRACTOR WITHOUT SPECIALTY CREWS NEEDING TO BE ON SITE. ENHANCED PUNCTURE RESISTANCE FROM AGGREGATE ON THE WATER SIDE AND PROTRUSIONS ON THE SOIL SIDE ARE ACHIEVED WITH THE PLACEMENT OF THE NON-WOVEN GEOTEXTILE ON EACH SIDE OF THE GEOMEMBRANE. SUFFICIENT TOPSOIL WILL BE PROVIDED ON TOP OF THE THERMOPLASTIC LINER THAT WILL ALLOW FOR PLANTINGS AND SEEDING TO BE PLACED ON TOP OF IT, THEREFORE THE BASIN WILL BE AESTHETICALLY PLEASING WHILE EFFECTIVE. THE CURRENT DESIGN WILL PROVIDE A 100% SEALED SYSTEM AND NO DIRECT CONNECTION FOR CONTAMINANTS TO ENTER THE CITY STORM SEWER AND ULTIMATELY THE HURON RIVER.




SYMBOL	DESCRIPTION
---	PROPERTY LINE
---	PROPOSED GRADING CONTOUR
---	PROPOSED GRADING RIDGELINE
---	PROPOSED STORMWATER STRUCTURES
---	PROPOSED STORMWATER PIPING
---	HIGH GROUNDWATER LIMITS OF FORMER UNDERGROUND STORAGE TANKS

- ### DRAINAGE AND UTILITY NOTES
- THE CONTRACTOR TO PERFORM A TEST PIT PRIOR TO CONSTRUCTION (RECOMMEND 30 DAYS PRIOR) AT LOCATIONS OF EXISTING UTILITY CROSSINGS FOR STORMWATER IMPROVEMENTS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IN WRITING.
  - CONTRACTOR SHALL START CONSTRUCTION OF STORM LINES AT THE LOWEST INVERT AND WORK UP GRADIENT.
  - THE CONTRACTOR IS REQUIRED TO CALL THE APPROPRIATE AUTHORITY FOR NOTICE OF CONSTRUCTION/EXCAVATION AND UTILITY MARK OUT PRIOR TO THE START OF CONSTRUCTION IN ACCORDANCE WITH STATE LAW. CONTRACTOR IS REQUIRED TO CONFIRM THE HORIZONTAL AND VERTICAL LOCATION OF UTILITIES IN THE FIELD. SHOULD A DISCREPANCY EXIST BETWEEN THE FIELD LOCATION OF A UTILITY AND THE LOCATION SHOWN ON THE PLAN SET OR SURVEY, THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IMMEDIATELY IN WRITING.
  - THE CONTRACTOR IS RESPONSIBLE TO MAINTAIN A RECORD OF THE AS-BUILT LOCATIONS OF ALL PROPOSED UNDERGROUND INFRASTRUCTURE. THE CONTRACTOR SHALL NOTE ANY DISCREPANCIES BETWEEN THE AS-BUILT LOCATIONS AND THE LOCATIONS DEPICTED WITHIN THE PLAN SET. THIS RECORD SHALL BE PROVIDED TO THE OWNER FOLLOWING COMPLETION OF WORK.

- ### EXCAVATION, SOIL PREPARATION, AND DEWATERING NOTES
- THE CONTRACTOR IS REQUIRED TO REVIEW THE REFERENCED GEOTECHNICAL DOCUMENTS PRIOR TO CONSTRUCTION. THESE DOCUMENTS SHALL BE CONSIDERED A PART OF THE PLAN SET.
  - THE CONTRACTOR IS REQUIRED TO PREPARE SUBGRADE SOILS BENEATH ALL PROPOSED IMPROVEMENTS AND BACKFILL ALL EXCAVATIONS IN ACCORDANCE WITH RECOMMENDATIONS BY THE GEOTECHNICAL ENGINEER OF RECORD.
  - THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING SHORING FOR ALL EXCAVATIONS AS REQUIRED. CONTRACTOR SHALL HAVE THE SHORING DESIGN PREPARED BY A QUALIFIED PROFESSIONAL SHORING DESIGNER. THESE SHALL BE SUBMITTED TO STONEFIELD ENGINEERING & DESIGN, LLC. AND THE OWNER PRIOR TO THE START OF CONSTRUCTION.
  - THE CONTRACTOR IS RESPONSIBLE FOR ENSURING THAT ALL OPEN EXCAVATIONS ARE PERFORMED AND PROTECTED IN ACCORDANCE WITH THE LATEST OSHA REGULATIONS.
  - THE CONTRACTOR IS RESPONSIBLE FOR ANY DEWATERING DESIGN AND OPERATIONS, AS REQUIRED, TO CONSTRUCT THE PROPOSED IMPROVEMENTS. THE CONTRACTOR SHALL OBTAIN ANY REQUIRED PERMITS FOR DEWATERING OPERATIONS AND GROUNDWATER DISPOSAL.

- ### STORMWATER INFILTRATION BMP CONSTRUCTION NOTES
- PRIOR TO THE START OF CONSTRUCTION, ANY AREA DESIGNATED TO BE USED FOR AN INFILTRATION BMP (E.G. BASIN, BIORETENTION AREA, ETC.) SHALL BE FENCED OFF AND SHALL NOT BE UTILIZED AS STORAGE FOR CONSTRUCTION EQUIPMENT OR AS A STOCKPILE AREA FOR CONSTRUCTION MATERIALS. NO ACTIVITY SHALL BE PERMITTED WITHIN THE INFILTRATION BASIN AREA UNLESS RELATED TO THE CONSTRUCTION OF THE INFILTRATION BASIN. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO NOTIFY ALL SUBCONTRACTORS OF BASIN AREA RESTRICTIONS.
  - THE CONTRACTOR SHALL MAKE EVERY EFFORT, WHERE PRACTICAL, TO AVOID SUBGRADE SOIL COMPACTION IN THE AREAS DESIGNATED TO BE USED FOR AN INFILTRATION BMP.
  - ALL EXCAVATION WITHIN THE LIMITS OF ANY INFILTRATION BMP SHALL BE PERFORMED WITH THE LIGHTEST PRACTICAL EXCAVATION EQUIPMENT. ALL EXCAVATION EQUIPMENT SHALL BE PLACED OUTSIDE THE LIMITS OF THE BASIN WHERE FEASIBLE. THE USE OF LIGHT-WEIGHT, RUBBER-TIRED EQUIPMENT (LESS THAN 8 PSI) APPLIED TO THE GROUND SURFACE IS RECOMMENDED WITHIN THE BASIN LIMITS.
  - THE SEQUENCE OF SITE CONSTRUCTION SHALL BE COORDINATED WITH BASIN CONSTRUCTION TO ADHERE TO SEQUENCING LIMITATIONS.
  - DURING THE FINAL GRADING OF AN INFILTRATION BASIN, THE BOTTOM OF THE BASIN SHALL BE DEEPLY TILLED WITH A ROTARY TILLER OR DISC HARROW AND THEN SMOOTHED OUT WITH A LEVELING DRAW OR EQUIVALENT GRADING EQUIPMENT. ALL GRADING EQUIPMENT SHALL BE LOCATED OUTSIDE OF THE BASIN BOTTOM WHERE FEASIBLE.
  - FOLLOWING CONSTRUCTION OF AN INFILTRATION BASIN, SOIL INFILTRATION TESTING BY A LICENSED GEOTECHNICAL ENGINEER IS REQUIRED TO CERTIFY COMPLIANCE WITH THE DESIGN INFILTRATION RATES IN ACCORDANCE WITH APPENDIX E OF THE NEW JERSEY DEPARTMENT OF ENVIRONMENTAL PROTECTION'S BEST MANAGEMENT PRACTICES MANUAL, LATEST EDITION. IF THE FIELD INFILTRATION RATES ARE LOWER THAN THE RATE USED DURING DESIGN, THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC. IN WRITING IMMEDIATELY TO DETERMINE THE APPROPRIATE COURSE OF ACTION.
  - THE CONTRACTOR SHALL NOTIFY THE MUNICIPALITY TO DETERMINE IF WITNESS TESTING IS REQUIRED DURING INFILTRATION BASIN EXCAVATION AND/OR SOIL INFILTRATION TESTING.



REVISIONS PER 3RD PLANNING REVIEW COMMENTS	REVISIONS PER 2ND PLANNING REVIEW COMMENTS	REVISIONS PER 1ST PLANNING REVIEW COMMENTS	DATE	BY	DESCRIPTION
5	4	3	10-30-2019	KHL	
4	3	2	10-11-2019	KHL	
3	2	1	08-22-2019	ADG	
2	1		08-08-2019	ADG	
1			05-30-2019	ADG	

NOT APPROVED FOR CONSTRUCTION

**STONEFIELD**  
engineering & design

Detroit, MI • New York, NY  
Princeton, NJ • Tampa, FL • Rochester, NY  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

SITE PLAN FOR CITY COUNCIL APPROVAL

**MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION**  
PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES

PARCEL ID: 09-09-30-3-18-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN

STATE OF MICHIGAN  
JAKE WHEATON  
6201068338  
MICHIGAN LICENSE NO. 6201068338  
LICENSED PROFESSIONAL ENGINEER

**STONEFIELD**  
engineering & design

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019  
TITLE: **STORMWATER MANAGEMENT PLAN**  
DRAWING: **C-5**



**SANITARY SEWER FLOW MITIGATION CALCULATIONS**  
(Based on City of Ann Arbor's Developer Offset-Mitigation Program Guidelines)

**DESIGN POPULATION**

2151 W. Stadium Blvd. will be a single story 3,803 SF Michigan Schools & Government Credit Union. Vehicular parking has been proposed as well as bicycle parking located near the front entrance.

**PROPOSED FLOW**


Based on the City of Ann Arbor's sanitary sewer flow evaluation Table 'A', the design dry weather flow rate for the development will be:

3,803 SF	Non-medical Office	0.06	gpd/gfa	=	228.18	gpd
Peak Flow =	228.18	x	4	x	1.2	= 1095.26 gpd
						= 0.76 gpm
						= 1.00 GPM

**FOOTING DRAIN DISCONNECT**

Mitigation peak flow =	0.76	gpm	/	4	=	0.19	FDD
						=	0

No mitigation required for flows <1.00 gpm. No footing drain disconnection required.



SYMBOL	DESCRIPTION
---	PROPERTY LINE
SAN	PROPOSED SANITARY LATERAL
W	PROPOSED DOMESTIC WATER SERVICE
E	PROPOSED ELECTRIC CONDUITS
G	PROPOSED GAS LINE
⊗	PROPOSED VALVE
⊕	PROPOSED FIRE HYDRANT
⊙	PROPOSED SANITARY MANHOLE / CLEANOUT
T	PROPOSED TRANSFORMER ON CONCRETE PAD WITH BOLLARDS


- DRAINAGE AND UTILITY NOTES**
- THE CONTRACTOR IS REQUIRED TO CALL THE APPROPRIATE AUTHORITY FOR NOTICE OF CONSTRUCTION/EXCAVATION AND UTILITY MARK OUT PRIOR TO THE START OF CONSTRUCTION IN ACCORDANCE WITH STATE LAW. CONTRACTOR IS REQUIRED TO CONFIRM THE HORIZONTAL AND VERTICAL LOCATION OF UTILITIES IN THE FIELD. SHOULD A DISCREPANCY EXIST BETWEEN THE FIELD LOCATION OF A UTILITY AND THE LOCATION SHOWN ON THE PLAN SET OR SURVEY, THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC IMMEDIATELY IN WRITING.
  - THE CONTRACTOR IS RESPONSIBLE TO PROTECT AND MAINTAIN IN OPERATION ALL UTILITIES NOT DESIGNATED TO BE REMOVED. THE CONTRACTOR IS RESPONSIBLE FOR REPAIRING ANY DAMAGE TO ANY EXISTING UTILITY IDENTIFIED TO REMAIN WITHIN THE LIMITS OF THE PROPOSED WORK DURING CONSTRUCTION.
  - A MINIMUM HORIZONTAL SEPARATION OF 10 FEET IS REQUIRED BETWEEN ANY SANITARY SEWER SERVICE AND ANY WATER LINES. IF THIS SEPARATION CANNOT BE PROVIDED, A CONCRETE ENCASUREMENT SHALL BE UTILIZED FOR THE SANITARY SEWER SERVICE AS APPROVED BY STONEFIELD ENGINEERING & DESIGN, LLC.
  - ALL WATER LINES SHALL BE VERTICALLY SEPARATED ABOVE SANITARY SEWER LINES BY A MINIMUM DISTANCE OF 18 INCHES. IF THIS SEPARATION CANNOT BE PROVIDED, A CONCRETE ENCASUREMENT SHALL BE UTILIZED FOR THE SANITARY SEWER SERVICE AS APPROVED BY STONEFIELD ENGINEERING & DESIGN, LLC.
  - THE CONTRACTOR TO PERFORM A TEST PIT PRIOR TO CONSTRUCTION (RECOMMEND 30 DAYS PRIOR) AT LOCATIONS OF EXISTING UTILITY CROSSINGS FOR WATER AND SANITARY SEWER CONNECTION IMPROVEMENTS. SHOULD A CONFLICT EXIST, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC IN WRITING.
  - THE CONTRACTOR IS RESPONSIBLE FOR COORDINATING GAS, ELECTRIC AND TELECOMMUNICATION CONNECTIONS WITH THE APPROPRIATE GOVERNING AUTHORITY.
  - CONTRACTOR SHALL START CONSTRUCTION OF ANY GRAVITY SEWER AT THE LOWEST INVERT AND WORK UP GRADIENT.
  - THE CONTRACTOR IS RESPONSIBLE TO MAINTAIN A RECORD SET OF PLANS REFLECTING THE LOCATION OF EXISTING UTILITIES THAT HAVE BEEN CAPPED, ABANDONED, OR RELOCATED BASED ON THE DESTRUCTION/REMOVAL ACTIVITIES REQUIRED IN THIS PLAN SET. THIS DOCUMENT SHALL BE PROVIDED TO THE OWNER FOLLOWING COMPLETION OF WORK.
  - THE CONTRACTOR IS RESPONSIBLE TO MAINTAIN A RECORD OF THE AS-BUILT LOCATIONS OF ALL PROPOSED UNDERGROUND INFRASTRUCTURE. THE CONTRACTOR SHALL NOTE ANY DISCREPANCIES BETWEEN THE AS-BUILT LOCATIONS AND THE LOCATIONS DISPICTED WITHIN THE PLAN SET. THIS RECORD SHALL BE PROVIDED TO THE OWNER FOLLOWING COMPLETION OF WORK.
  - THE CONTRACTOR SHALL INSTALL THE FIRE HYDRANT WITH THE OUTLETS DIRECTED TOWARDS WEST STADIUM BOULEVARD.

**KNOX BOX TO BE PROVIDED. LOCATION TO BE PROVIDED PER ARCHITECTURAL DRAWINGS AND APPROVED BY THE FIRE MARSHAL.**

**NO FIREWALL IS REQUIRED AND WILL NOT BE PROVIDED WITHIN THE PROPOSED BUILDING**

**NO BOOSTER PUMP NEEDED FOR DOMESTIC WATER CONNECTION**

**NO FIRE SUPPRESSION SYSTEM REQUIRED**



NO.	DATE	ISSUE	DESCRIPTION
5	10-30-2019	KHL	REVISIONS PER 3RD PLANNING REVIEW COMMENTS
4	10-11-2019	KHL	REVISIONS PER 2ND PLANNING REVIEW COMMENTS
3	08-22-2019	ADG	REVISIONS PER 2ND PLANNING REVIEW COMMENTS
2	08-08-2019	ADG	REVISIONS PER 1ST PLANNING REVIEW COMMENTS
1	05-30-2019	ADG	SUBMISSION FOR SITE PLAN APPROVAL

**NOT APPROVED FOR CONSTRUCTION**

**STONEFIELD**  
engineering & design

Detroit, MI • New York, NY  
Princeton, NJ • Tampa, FL • Rutherford, NJ  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

**SITE PLAN FOR CITY COUNCIL APPROVAL**

**MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION**

**PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES**

PARCEL ID: 09-09-30-318-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN

STATE OF MICHIGAN  
JAKE ROBERTSON  
6201068338  
MICHIGAN LICENSE No. 6201068338  
LICENSED PROFESSIONAL ENGINEER

**STONEFIELD**  
engineering & design

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019

TITLE: **UTILITY PLAN**


DRAWING: **C-7**




PROPOSED LUMINARIES SCHEDULE								
SYMBOL	LABEL	QUANTITY	SECURITY LIGHTING	DISTRIBUTION	LLF	WATTS	MANUFACTURER	IES FILE
	A	2	D-SERIES SIZE I LED AREA LUMINAIRE	II	0.90	70	LITHONIA LIGHTING	DSX1_LED_P2_40K_T4M_MVOLT_HS
	B	1	D-SERIES SIZE I LED AREA LUMINAIRE	IV	0.90	70	LITHONIA LIGHTING	DSX1_LED_P2_40K_T4M_MVOLT_HS
	C	4	KACM LED SURFACE LUMINAIRE	V	0.90	46	LITHONIA LIGHTING	KACM_LED_20C_700_40K_R5_MVOLT
	D	3	WST LED ARCHITECTURAL WALL SCONCE	VW	0.90	30	LITHONIA LIGHTING	WST_LED_P2_40K_VW_MVOLT_VG

LIGHTING REQUIREMENTS		
CODE SECTION	REQUIRED	PROPOSED
§ 5252	ALL EXTERIOR LIGHTING SHALL BE ADEQUATELY SHIELDED SO THAT LIGHT IS DIRECTED AWAY FROM PUBLIC RIGHT-OF-WAYS AND ADJACENT PROPERTIES.	COMPLIES
§ 5243	MINIMUM ILLUMINATION LEVELS: PARKING LOTS - 0.6 FOOTCANDLES BICYCLE PARKING - 0.4 FOOTCANDLES MAX UNIFORMITY RATIO - 10:1	COMPLIES

SYMBOL	DESCRIPTION
	PROPOSED CALCULATION AREA
	PROPOSED LIGHTING FIXTURE (MOUNTING HEIGHT)
	PROPOSED LIGHTING INTENSITY (FOOTCANDLES)
	PROPOSED AREA LIGHT
	PROPOSED BUILDING MOUNTED LIGHT



- GENERAL LIGHTING NOTES**
- THE LIGHTING LEVELS DEPICTED WITHIN THE PLAN SET ARE CALCULATED UTILIZING DATA OBTAINED FROM THE LISTED MANUFACTURER. ACTUAL ILLUMINATION LEVELS AND PERFORMANCE OF ANY PROPOSED LIGHTING FIXTURE MAY VARY DUE TO UNCONTROLLABLE VARIABLES SUCH AS WEATHER, VOLTAGE SUPPLY, LAMP TOLERANCE, EQUIPMENT SERVICE LIFE AND OTHER VARIABLE FIELD CONDITIONS.
  - WHERE APPLICABLE, THE EXISTING LIGHT LEVELS DEPICTED WITHIN THE PLAN SET SHALL BE CONSIDERED APPROXIMATE. THE EXISTING LIGHT LEVELS ARE BASED ON FIELD OBSERVATIONS AND THE MANUFACTURER'S DATA OF THE ASSUMED OR MOST SIMILAR LIGHTING FIXTURE MODEL.
  - UNLESS NOTED ELSEWHERE WITHIN THIS PLAN SET, THE LIGHT LOSS FACTORS USED IN THE LIGHTING ANALYSIS ARE AS FOLLOWS:
    - LIGHT EMITTING DIODES (LED): 0.90
    - HIGH PRESSURE SODIUM: 0.72
    - METAL HALIDE: 0.72
  - THE CONTRACTOR SHALL NOTIFY STONEFIELD ENGINEERING & DESIGN, LLC IN WRITING, PRIOR TO THE START OF CONSTRUCTION, OF ANY PROPOSED LIGHTING LOCATIONS THAT CONFLICT WITH EXISTING PROPOSED DRAINAGE, UTILITY, OR OTHER IMPROVEMENTS. THE CONTRACTOR IS RESPONSIBLE TO PREPARE A WIRING PLAN AND PROVIDE ELECTRIC SERVICE TO ALL PROPOSED LIGHTING FIXTURES. THE CONTRACTOR IS REQUIRED TO PREPARE AN AS-BUILT PLAN OF WIRING AND PROVIDE COPIES TO THE OWNER AND STONEFIELD ENGINEERING & DESIGN, LLC.



REVISION	DATE	ISSUE	BY	DESCRIPTION
5	10-30-2019	KHL		REVISIONS PER 3RD PLANNING REVIEW COMMENTS
4	10-11-2019	ADG		REVISIONS PER 2ND PLANNING REVIEW COMMENTS
3	08-22-2019	ADG		REVISIONS PER PLANNING REVIEW COMMENTS
2	08-08-2019	ADG		REVISIONS PER PLANNING REVIEW COMMENTS
1	05-30-2019	ADG		SUBMISSION FOR SITE PLAN APPROVAL

NOT APPROVED FOR CONSTRUCTION

**STONEFIELD**  
engineering & design

Detroit, MI • New York, NY  
Princeton, NJ • Tampa, FL • Rochester, NY  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

SITE PLAN FOR CITY COUNCIL APPROVAL

**MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION**  
PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES

PARCEL ID: 09-09-30-3-18-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN



**STONEFIELD**  
engineering & design

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019

TITLE: LIGHTING PLAN

DRAWING: C-8

PLANT SCHEDULE					
PLANT KEY	QUANTITY	BOTANICAL NAME	COMMON NAME	SIZE	REMARKS
<b>DECIDUOUS TREES (TOTAL 11)</b>					
QUE. RUB.	7	QUERCUS RUBRA	NORTHERN RED OAK	2.5" CAL	B&B
MAL. RED.	4	MALUS 'RED BARON'	RED BARON CRAB APPLE	2.5" CAL	B&B
<b>EVERGREEN SHRUBS (TOTAL 72)</b>					
TAX. DEN.	16	TAXUS MEDIA 'DENSIFORMIS'	DENSE YEW	2'-0"	CONT.
TAX. MOO.	56	TAXUS MEDIA 'MOON'	MOON YEW	2'-4"	B&B
<b>DECIDUOUS SHRUBS (TOTAL 91)</b>					
RED. SPR.	48	ILEX VERTICILLATA 'RED SPRITE'	RED SPRITE WINTERBERRY	30"	B&B
ARO. MEL.	43	ARONIA MELANOCARPA	BLACK CHOKEBERRY	30"	B&B
<b>PERENNIALS (TOTAL 159)</b>					
SCL. ACU.	84	SCIRPUS ACUTUS	HARD STEM BULRUSH	4"	BARE ROOT
SPL. JAP.	74	SPIREA JAPONICA 'LITTLE PRINCESS'	LITTLE PRINCESS SPIREA	1'-6"	CONT.
HYD. PAN.	1	HYDRANGEA PANICULATA 'LIMELIGHT'	LIMELIGHT HARDY HYDRANGEA	5 GAL	CONT.
<b>GROUND COVER (TOTAL 65)</b>					
FES. GLA.	21	FESTUCA GLAUCA 'ELIJAH BLUE'	ELIJAH BLUE FESCUE	1 GAL	CONT.
SCH. SCO.	44	SCHIZACHYRIUM SCOPARIOM	LITTLE BLUESTEM	1 GAL	CONT.

NOTE: IF ANY DISCREPANCIES OCCUR BETWEEN AMOUNTS SHOWN ON THE LANDSCAPE PLAN AND WITHIN THE PLANT LIST, THE PLAN SHALL DICTATE.

LANDSCAPING AND BUFFER REQUIREMENTS		
CODE SECTION	REQUIRED	PROPOSED
§ 5.20.3-A.1	PARKING AREA BUFFER WIDTH: MINIMUM 10 FT BUFFER STRIP BETWEEN PARKING AREA AND RIGHT-OF-WAY	10 FT
§ 5.20.3-A.2	PARKING AREA BUFFER: 1 DECIDUOUS SHADE TREE OR EVERGREEN TREE PER 30 FT OF PUBLIC RIGHT-OF-WAY (140 LF)(130 LF) = 5 TREES	5 TREES
§ 5.20.3-A.3	PARKING AREA SCREENING: A 30 INCH HIGH SCREENING WALL OR HEDGE ROW SHALL BE PLACED WITHIN THE FRONT LANDSCAPE AREA ALONG THE PARKING AREA	PROVIDED
§ 5.20.3-B.1	INTERIOR LANDSCAPE ISLANDS: 1 SF PER 30 SF OF PARKING AREA	COMPLIES
§ 5.20.3-B.2	MINIMUM 165 SF PER ISLAND (15,934 SF) X (1/20 SF) = 797 SF REQUIRED	1,791 SF
§ 5.20.3-B.5	1 DECIDUOUS SHADE TREE PER 250 SF REQUIRED (797 SF) X (1/250 SF) = 4 TREES	4 TREES

TREE KEY		
PLANT KEY	PLANT KEY	COMMON NAME
	QUE. RUB.	NORTHERN RED OAK
	MAL. RED.	RED BARON CRAB APPLE

**IRRIGATION NOTES:**  
IRRIGATION CONTRACTOR TO PROVIDE A DESIGN FOR AN IRRIGATION SYSTEM SEPARATING PLANTING BEDS FROM LAWN AREA. PRIOR TO CONSTRUCTION, DESIGN IS TO BE SUBMITTED TO THE PROJECT LANDSCAPE DESIGNER FOR REVIEW AND APPROVAL. WHERE POSSIBLE, DRIP IRRIGATION AND OTHER WATER CONSERVATION TECHNIQUES SUCH AS RAIN SENSORS SHALL BE IMPLEMENTED. CONTRACTOR TO VERIFY MAXIMUM ON SITE DYNAMIC WATER PRESSURE AVAILABLE MEASURED IN PSI. PRESSURE REDUCING DEVICES OR BOOSTER PUMPS SHALL BE PROVIDED TO MEET SYSTEM PRESSURE REQUIREMENTS. DESIGN TO SHOW ALL VALVES, PIPING, HEADS, BACKFLOW PREVENTION METERS, CONTROLLERS, AND SLEEVES WITHIN HARDSCAPE AREAS.



**LANDSCAPING NOTES:**  
1. THE CONTRACTOR SHALL RESTORE ALL DISTURBED GRASS AND LANDSCAPED AREAS TO MATCH EXISTING CONDITIONS UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET.  
2. THE CONTRACTOR SHALL RESTORE ALL DISTURBED LAWN AREAS WITH A MINIMUM 4 INCH LAYER OF TOPSOIL AND SEED.  
3. THE CONTRACTOR SHALL RESTORE MULCH AREAS WITH A MINIMUM 3 INCH LAYER OF MULCH.  
4. THE MAXIMUM SLOPE ALLOWABLE IN LANDSCAPE RESTORATION AREAS SHALL BE 3 FEET HORIZONTAL TO 1 FOOT VERTICAL (3:1 SLOPE) UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET.  
5. THE CONTRACTOR IS REQUIRED TO LOCATE ALL SPRINKLER HEADS IN AREA OF LANDSCAPING DISTURBANCE PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL RELOCATE SPRINKLER HEADS AND LINES IN ACCORDANCE WITH OWNER'S DIRECTION WITHIN AREAS OF DISTURBANCE.  
6. THE CONTRACTOR SHALL ENSURE THAT ALL DISTURBED LANDSCAPED AREAS ARE GRADED TO MEET FLUSH AT THE ELEVATION OF WALKWAYS AND TOP OF CURB ELEVATIONS EXCEPT UNLESS INDICATED OTHERWISE WITHIN THE PLAN SET. NO ABRUPT CHANGES IN GRADE ARE PERMITTED IN DISTURBED LANDSCAPING AREAS.  
7. ALL DISEASED, DAMAGED OR DEAD MATERIAL TO BE REPLACED ACCORDING TO THE STANDARDS OUTLINED WITHIN CHAPTER 55 OF THE ANN ARBOR UNIFIED DEVELOPMENT CODE FOR THE DURATION OF THE SITE PLAN.  
8. ALL PLANT SPECIES DEVIATIONS FROM THE APPROVED SITE PLAN MUST BE APPROVED BY THE CITY OF ANN ARBOR PRIOR TO INSTALLATION.


**SNOW REMOVAL NOTES:**  
1. SNOW SHALL NOT BE STORED WITHIN ANY INTERIOR LANDSCAPED ISLAND OR WITHIN ANY AREA DESIGNATED FOR PARKING OR LOADING.

**FERTILIZATION NOTE:**  
1. APPLICATIONS OF FERTILIZER BEYOND THE INITIAL TOPSOIL AND SEEDING SHALL BE FERTILIZER WITH NO PHOSPHOROUS.

**SOIL COMPACTION NOTE:**  
1. ONCE FINE GRADING HAS BEEN COMPLETED, HEAVY MACHINERY SHALL NOT BE USED WITHIN PLANTING AREAS TO PREVENT COMPACTION. IN ALL PLANTING AREAS WHERE SOIL COMPACTION HAS OCCURRED DURING CONSTRUCTION, SOIL SHALL BE TILLED TO THE DEPTH OF THE PROPOSED ROOT BALL OF THE PLANTINGS OR 4" DEPTH FOR SEEDED AREAS PRIOR TO THE PLANTING.  
2. OVER EXCAVATE SIDES OF PLANTING PITS IN COMPACTED SOIL AREAS.


**STORMWATER DETENTION POND TOPSOIL TO BE AMENDED WITH ORGANIC MATERIAL SOILS AND MUST BE FREE OF CONSTRUCTION DEBRIS AND SUBSOILS. THE SOIL SHALL CONTAIN BETWEEN 20-30 PERCENT COMPOST.**





**LOCATION MAP**

SCALE: 1" = 2,000'±



**STABILIZED CONSTRUCTION ENTRANCE DETAIL**

NOT TO SCALE

**PERMANENT MAINTENANCE TASKS AND SCHEDULE**


	COMPONENTS						Schedule
	Streets	Storm Sewer System	Catch Basin Sumps	Catch Basin Inlets	Detention Basin	Outflow Control Structure	
Inspect for sediment accumulation	X	X	X	X	X	X	Annually
Removal of sediment accumulation		X	X	X	X	X	As needed
Inspect for floatables & debris		X	X	X	X	X	Annually
Cleaning of floatables & debris		X	X	X	X	X	Annually
Inspect for erosion					X		Annually
Re-establish permanent vegetation on eroded slopes					X		As needed
Clean streets	X						Semi-Annually

**SEQUENCE OF CONSTRUCTION**

1. INSTALL AND MAINTAIN SOIL EROSION CONTROL MEASURES AS REQUIRED (90 DAYS).
2. ROUGH GRADING AND TEMPORARY SEEDING (30 DAYS).
3. EXCAVATE AND INSTALL UTILITIES (30 DAYS).
4. CONSTRUCT RIGHT OF WAY IMPROVEMENTS (7 DAYS).
5. BUILDING CONSTRUCTION AND SITE IMPROVEMENTS (120 DAYS).
6. LANDSCAPING IMPROVEMENTS AND FINAL SEEDING (7 DAYS).
7. REMOVE SOIL EROSION MEASURES AND CLEANUP SITE (1 DAY).

NOTE: TIME DURATIONS ARE APPROXIMATE AND ARE INTENDED TO ACT AS A GENERAL GUIDE TO THE CONSTRUCTION TIMELINE. ALL DURATIONS ARE SUBJECT TO CHANGE BY CONTRACTOR. CONTRACTOR SHALL SUBMIT CONSTRUCTION SCHEDULE TO TOWNSHIP AND ENGINEER. CONTRACTOR SHALL PHASE CONSTRUCTION ACCORDINGLY.

NOTE: STORMWATER MANAGEMENT SYSTEM TO BE INSTALLED AND APPROVED PRIOR TO RELEASE OF BUILDING PERMIT.



**SOIL STOCKPILE DETAIL**

NOT TO SCALE

**SOIL EROSION AND SEDIMENT CONTROL NOTES**

1. THE CONTRACTOR IS RESPONSIBLE FOR SOIL EROSION AND SEDIMENT CONTROL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REQUIREMENTS.
2. THE CONTRACTOR IS RESPONSIBLE FOR DUST CONTROL AND COMPLIANCE WITH LOCAL, STATE, AND FEDERAL AIR QUALITY STANDARDS.
3. THE CONTRACTOR IS RESPONSIBLE TO INSPECT ALL SOIL EROSION MEASURES WEEKLY AND AFTER A PRECIPITATION EVENT GREATER THAN 1 INCH. THE CONTRACTOR SHALL MAINTAIN AN INSPECTION LOG ON SITE AND DOCUMENT CORRECTIVE ACTION AS REQUIRED TAKEN THROUGHOUT THE COURSE OF CONSTRUCTION.
4. THE CONTRACTOR SHALL NOT ALLOW BUILD-UP OF DIRT OR SEDIMENT ON WEST STADIUM BOULEVARD. THE CONTRACTOR SHALL PROVIDE SWEEPING OF THE ROADWAY ON WEST STADIUM BOULEVARD AS NECESSARY.
5. THE SOIL EROSION CONTROLS WILL BE MAINTAINED WEEKLY AND AFTER EVERY STORM EVENT BY THE CONTRACTOR.

**EARTHWORK ESTIMATE**

THE EARTHWORK ESTIMATE ON SITE WILL CONSIST OF 16,000 CF OF EXCAVATION FOR THE DETENTION BASIN. ALL EXCAVATION SOILS WILL REMAIN ON SITE.

**SOIL CHARACTERISTICS CHART**

TYPE OF SOIL	WawabB - WAWASEE LOAM
PERCENT OF SITE COVERAGE	74.6%
HYDROLOGIC SOIL GROUP	B
DEPTH TO RESTRICTIVE LAYER	MORE THAN 80 INCHES
SOIL PERMEABILITY	0.60 TO 2.00 IN / HR
DEPTH TO WATER TABLE	MORE THAN 80 INCHES

**SOIL CHARACTERISTICS CHART**





TYPE OF SOIL	WawabC - WAWASEE LOAM
PERCENT OF SITE COVERAGE	25.4%
HYDROLOGIC SOIL GROUP	B
DEPTH TO RESTRICTIVE LAYER	MORE THAN 80 INCHES
SOIL PERMEABILITY	0.60 TO 2.00 IN / HR
DEPTH TO WATER TABLE	MORE THAN 80 INCHES

**SOIL EROSION CONTROL COST ESTIMATE**

Description	Quantity	Unit	Unit Price	Total
Silt Fence	901	LF	\$2.00	\$1,802
Inlet Filters	10	EA	\$150.00	\$1,500
Rip-Rap - 6" Diameter	1	EA	\$350.00	\$350
Seeding and Mulching	0.40	AC	\$3,500.00	\$1,400

**SYMBOL DESCRIPTION**

---	PROPERTY BOUNDARY
- - - -	ADJACENT PROPERTY BOUNDARY
---	LOD
---	SF
[Symbol]	PROPOSED STOCKPILE & EQUIPMENT STORAGE
[Symbol]	PROPOSED STABILIZED CONSTRUCTION ENTRANCE
[Symbol]	PROPOSED INLET PROTECTION FILTER



**REVISIONS**

REV. NO.	DATE	BY	DATE
1	11-6-92	SSJ/DF	

**PUBLIC SERVICES DEPARTMENT**  
CITY OF ANN ARBOR

**SILT FENCE**

DR. BY: DF/SSJ, CHK. BY: CSS/DF, DRAWING NO.: SD-EC-3  
SCALE: NONE, DATE: 11-6-92, SHEET NO.: OF

GRAPHIC SCALE IN FEET  
1" = 20'

**STONEFIELD engineering & design**

REVISIONS PER 3RD PLANNING REVIEW COMMENTS: 5  
REVISIONS PER 2ND PLANNING REVIEW COMMENTS: 4  
REVISIONS PER 1ST PLANNING REVIEW COMMENTS: 3  
SUBMISSION FOR SITE PLAN APPROVAL: 2

**NOT APPROVED FOR CONSTRUCTION**

**STONEFIELD engineering & design**

Detroit, MI • New York, NY  
Princeton, NJ • Tampa, FL • Rutherford, NJ  
www.stonefielddesign.com

607 Shelby Suite 200, Detroit, MI 48226  
Phone 248.247.1115

**SITE PLAN FOR CITY COUNCIL APPROVAL**

**MICHIGAN SCHOOLS & GOVERNMENT CREDIT UNION**

**PROPOSED CREDIT UNION WITH DRIVE-THRU FACILITIES**

PARCEL ID: 09-09-30-318-028  
2151 WEST STADIUM BOULEVARD  
CITY OF ANN ARBOR  
WASHTENAW COUNTY, MICHIGAN

**STATE OF MICHIGAN**  
JAKE JOHNSON  
6201088338  
MICHIGAN LICENSE No. 6201088338  
LICENSED PROFESSIONAL ENGINEER

**STONEFIELD engineering & design**

SCALE: 1" = 20' PROJECT ID: M-19060  
CITY OF ANN ARBOR PROJECT NUMBER: SP19-019

**TITLE: SOIL EROSION & SEDIMENT CONTROL PLAN**

DRAWING: **C-10**







**GENERAL TREE PLANTING NOTES:**

- FOR CONTAINER GROWN TREES USE FINGERS OR SMALL HAND TOOLS TO PULL THE ROOTS OUT OF THE OUTER LAYER OF POTTING SOIL THEN CUT OR PULL APART ANY ROOT CIRCLING THE PERIMETER OF THE CONTAINER.
- INCORPORATE COMMERCIALY PREPARED MYCORRHIZAE SPORES AND FERTILIZER TABLETS IN THE SOIL IMMEDIATELY AROUND THE ROOT BALL AT RATE SPECIFIED BY THE MANUFACTURER.
- THOROUGHLY SOAK THE ROOT BALL AND THE ADJACENT PREPARED SOIL SEVERAL TIMES DURING THE FIRST MONTH AFTER PLANTING AND REGULARLY THROUGHOUT THE FOLLOWING TWO GROWING SEASONS. WHEN IRRIGATION IS NOT PROVIDED SPECIFICALLY FOR THE TREE, IT IS RECOMMENDED THAT GATOR BAGS ARE USED TO HELP FACILITATE THE PROPER AMOUNT AND RATE OF WATER ARE ACHIEVED. GATOR BAGS SHALL BE INSTALLED AT THE BEGINNING OF EACH GROWING SEASON AND REMOVED EACH FALL. THIS WILL ALLOW FOR THE AREA BENEATH THE GATOR BAG TO DRY OUT REDUCING THE GROWTH OF FUNGUS AND REMOVE POSSIBLE HIDING SPOTS FOR RODENTS. THE GATOR BAGS WILL BE REMOVED AT THE END OF THE SECOND GROWING SEASON UNLESS OTHERWISE ADVISED.
- PRIOR TO DIGGING HOLE, REMOVE ALL EXCESS SOIL FROM ROOT FLARE TO DETERMINE DEPTH OF HOLE. REFER TO THE ROOT FLARE DETAIL.
- WHEN PLANTING IN WINTER OR ON WINDY SITES APPLY ANTI-DESSICANT AS PER MANUFACTURER'S SPECIFICATIONS.

**PLANT MATERIAL SELECTION AND HANDLING NOTES:**

- PLANTS WITH UNDERSIZED OR BROKEN ROOT BALLS, EXCESSIVE CURLING AND/OR GIRDLING OF ROOTS, INJURY FROM ROUGH TREATMENT, OR DROUGHT STRESS WILL BE REJECTED.
- IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO GUARANTEE THAT THE ROOT BALLS ARE PROPERLY SIZED. PLEASE BE AWARE THAT FOR PROPER SIZING, UNSUITABLE SOIL MATERIAL SHALL BE REMOVED PRIOR TO DIGGING. REFER TO THE TREE ROOT FLARE DETAIL.
- ROOT BALLS SHALL BE KEPT MOIST AT ALL TIMES.
- PLANTS SHALL BE COVERED DURING TRANSPORT TO PREVENT EXCESSIVE DRYING FROM WIND. IN WARM WEATHER PLANTS SHALL BE COVERED JUST PRIOR TO TRAVEL AND UNCOVERED IMMEDIATELY UPON REACHING DESTINATION TO AVOID HEAT BUILD UP UNDER THE TARP. PLANT MATERIAL SHALL NOT BE LEFT IN DIRECT SUNLIGHT OR ON HIGH HEAT ABSORPTION MATERIALS, SUCH AS BUT NOT LIMITED TO, ASPHALT AND/OR METAL TRUCK BEDS TO PREVENT THE WILTING OF MATERIAL.
- TREES SHALL BE MOVED BY THEIR ROOT BALL NOT THEIR TRUNK. TREES LARGER THAN 6" SHALL BE MOVED WITH PROPER STRAPPING SECURING ROOT BALL TO EQUIPMENT. WEAVE STRAPPING THROUGH THE LACING, NOT AROUND THE TRUNK. TREE TRUNK SHALL BE PROTECTED AT ALL TIME FROM COMPRESSION AND SEARING.
- IF PLANTS ARE NOT PLANTED IMMEDIATELY ON SITE, PROPER CARE SHALL BE TAKEN:
  - PLACE IN PARTIAL SHADE WHEN POSSIBLE.
  - COVER ROOT BALL WITH MOISTENED MULCH OR AGED WOODCHIPS.
  - SUPPLY PROPER IRRIGATION AS NOT TO ALLOW THE ROOT BALL TO DRY OUT.
  - UNTIE PLANT MATERIAL AND ALLOW PROPER SPACING OF PLANTS FOR AIR CIRCULATION TO PREVENT DISEASE, WILTING, LEAF LOSS AND GENERAL HEATH OF PLANTS.

**BARE ROOT TREE PLANTING NOTES:**

- SUBMERGE ROOTS IN ROOT DIP GEL. BARE ROOT PLANTING AID WITH MYCORRHIZA OR APPROVED EQUAL.
 

MIXING DIRECTIONS:

  - EMPTY THE CONTENTS OF THIS PACKAGE IN FOUR GALLONS OF WATER.
  - LET MIX STAND FOR TEN MINUTES, STIRRING OCCASIONALLY. THE PRODUCT WILL FORM A SLURRY OR THICK MIXTURE, SO THE ACTIVE INGREDIENTS WILL ADHERE TO THE ROOTS.
  - DIP EACH PLANT FOR ABOUT 5 SECONDS. PLANT IMMEDIATELY. THERE IS NO HARM IN LEAVING THE PLANT IN THE MIX. FOUR GALLONS OF MIX WILL TREAT 100-500 PLANTS. THE NUMBER OF PLANTS DEPENDS ON ROOT MASS AND HOW MUCH OF THE MIXTURE THE ROOTS OF YOUR PLANTS ABSORB. THE ENDO AND ECTOMYCORRHIZA WILL BE USEFUL ON ALMOST ALL PLANTS. THE MAJOR EXCEPTIONS ARE RHODODENDRONS AND AZALEAS BUT THE ROOTS28 BIOSTIMULANT AND THE WATER HOLDING GEL WILL STILL BE BENEFICIAL.
- CUT OFF ALL BROKEN ROOTS.
- MAKE FRESH CUTS AT ENDS OF ROOTS.
- DIG PLANT HOLES AT LEAST 3 X THE WIDTH AND DEPTH OF THE ROOT MASS.
- PLANT ROOT FLARE AT GRADE OR GRAFT JUST ABOVE GRADE.
- BACK FILL ALL HOLES WITH PLANTING MIX APPROVED BY THE ENGINEER.

**PLANT MATERIAL GUARANTEE NOTES:**



- LANDSCAPE CONTRACTOR SHALL SUPPLY A TWO YEAR PLANT MATERIAL GUARANTEE.
- CONTRACTOR SHALL NOT BE RESPONSIBLE FOR THE PLANTINGS IF OWNER FAILS TO PROVIDE PROPER CARE AND WATERING AS INSTRUCTED BY THE LANDSCAPE CONTRACTOR DURING GUARANTEE PERIOD.
- CONTRACTOR SHALL INSTRUCT OWNER AS TO PROPER CARE OF MATERIAL.
- THE LANDSCAPE PLAN DRAWING SET SHALL BE CONSIDERED AN INTEGRAL PART OF THE SITE PLAN APPROVAL AND SHALL BE MAINTAINED IN PERPETUITY.

**SOIL PREPARATION NOTES:**

- THE QUALITY OF SOIL AVAILABLE FOR PLANTING VARIES WIDELY FROM SITE TO SITE, ESPECIALLY AFTER CONSTRUCTION ACTIVITY HAS OCCURRED. THE NATURE OF CONSTRUCTION RESULTS IN COMPACTION, FILLING, CONTAMINATION, AND GRADING OF THE ORIGINAL SOIL ON A SITE, RAPIDLY MAKING IT UNSUITABLE FOR PLANTING. PREVIOUS HUMAN ACTIVITY AT A SITE CAN ALSO AFFECT THE ABILITY OF THE SOIL TO SUPPORT PLANTS.
- WHENEVER POSSIBLE THE SOIL IMPROVEMENT AREA SHOULD BE CONNECTED FROM TREE TO TREE.
- ALWAYS TEST SOIL FOR PH, NUTRIENT LEVELS, AND TEXTURAL CLASS AND ADJUST THESE AS REQUIRED. SUBMIT TEST RESULTS TO THE ENGINEER PRIOR TO PLANTING ALONG WITH SOIL IMPROVEMENT SUGGESTIONS. SOIL TESTS CAN BE ACQUIRED FROM YOUR LOCAL COUNTY AGRICULTURAL EXTENSION OR AT RUTGERS COOPERATIVE EXTENSION 732-932-9295.
- LOOSEN SOIL WITH A BACK HOE OR OTHER LARGE COARSE-TILING EQUIPMENT WHEN POSSIBLE, THIS SHOULD NOT BE PERFORMED WHEN SOIL IS FROZEN OR EXCESSIVELY WET. TILING THAT PRODUCES LARGE, COARSE CHUNKS OF SOIL IS PREFERABLE TO TILING THAT RESULTS IN FINE GRAINS UNIFORM IN TEXTURE. AFTER AREA IS LOOSEN IT SHALL NOT BE DRIVEN BY ANY VEHICLE.
- ANY OVER BY APPLY PRE-EMERGENT WEED CONTROL TO ALL PLANT BEDS PRIOR TO MULCHING. ENSURE COMPATIBILITY BETWEEN PRODUCT AND PLANT MATERIAL.
- PLANT BED/TREE PIT DRAINAGE: LANDSCAPE CONTRACTOR SHALL BE RESPONSIBLE FOR PROPER SURFACE AND SUBSURFACE PLANT BED DRAINAGE PRIOR TO INSTALLATION OF PLANTS. IF POOR DRAINAGE CONDITIONS EXIST, CORRECTIVE ACTION SHALL BE TAKEN PRIOR TO PLANTING.
- ALL PLANTING SOIL SHALL BE AMENDED WITH THE FOLLOWING:
  - MYCORB® TREE SAVER - IS A DRY GRANULAR MYCORRHIZAL FUNGI INOCULANT THAT IS MIXED IN THE BACKFILL WHEN PLANTING TREES AND SHRUBS. IT CONTAINS SPORES OF BOTH ECTOMYCORRHIZAL AND VA MYCORRHIZAL FUNGI (VAM), BENEFICIAL RHIZOSPHERE BACTERIA, TERRA-SORB SUPERABSORBENT HYDROGEL TO REDUCE WATER LEACHING, AND SELECTED ORGANIC MICROBIAL NUTRIENTS. DIRECTIONS FOR USE: USE 3-OZ PER EACH FOOT DIAMETER OF THE ROOT BALL OR 3-OZ PER INCH CALIBER. MIX INTO THE BACKFILL WHEN PLANTING TREES AND SHRUBS. MIX PRODUCT IN A RING-SHAPED VOLUME OF SOIL AROUND THE UPPER PORTION OF THE ROOT BALL, EXTENDING FROM THE SOIL SURFACE TO A DEPTH OF ABOUT 8-INCHES (20-CM), AND EXTENDING OUT FROM THE ROOT BALL ABOUT 8-INCHES (20-CM) INTO THE BACKFILL. APPLY WATER TO SOIL SATURATION. COMPATIBILITY: SPECIES: MYCORB® TREE SAVER® IS EFFECTIVE FOR ALL TREE AND SHRUB SPECIES EXCEPT RHODODENDRONS, AZALEAS, AND MOUNTAIN LAUREL, WHICH REQUIRE ERICOID MYCORRHIZAE. USE OF TREE SAVER® WITH THESE SPECIES WILL NOT HARM THEM. SOIL PH: THE FUNGI IN THIS PRODUCT WERE CHOSEN BASED ON THEIR ABILITY TO SURVIVE AND COLONIZE PLANT ROOTS IN A PH RANGE OF 3 TO 9. FUNGICIDES: THE USE OF CERTAIN FUNGICIDES CAN HAVE A DETRIMENTAL EFFECT ON YOUR INOCULATION PROGRAM. SOIL APPLICATION OF ANY FUNGICIDE IS NOT RECOMMENDED FOR TWO WEEKS AFTER APPLICATION. OTHER PESTICIDES: HERBICIDES AND INSECTICIDES DO NOT NORMALLY INTERFERE WITH MYCORRHIZAL FUNGAL DEVELOPMENT, BUT MAY INHIBIT THE GROWTH OF SOME TREE AND SHRUB SPECIES IF NOT USED PROPERLY.
  - HEALTHY START MACRO TABS 12-8-8 FERTILIZER TABLETS ARE PLACED IN THE UPPER 4 INCHES OF BACKFILL SOIL WHEN PLANTING TREES AND SHRUBS. TABLETS ARE FORMULATED FOR LONG-TERM RELEASE BY SLOW BIODEGRADATION, AND LAST UP TO 2 YEARS AFTER PLANTING. TABLETS CONTAIN 12-8-8 NPK FERTILIZER, AS WELL AS A MINIMUM OF SEVEN PERCENT (7%) HUMIC ACID BY WEIGHT, MICROBIAL NUTRIENTS DERIVED FROM SEA KELP, PROTEIN BYPRODUCTS, AND YUCCA SCHIDIGERA AND A COMPLEMENT OF BENEFICIAL RHIZOSPHERE BACTERIA. THE STANDARD 21 GRAM TABLET IS SPECIFIED HERE. DIRECTIONS FOR USE FOR PLANTING BALLED & BURLAPPED (B&B) TREES AND SHRUBS: MEASURE THE THICKNESS OF THE TRUNK, AND USE ABOUT 1 TABLET (21-G) PER HALF-INCH. PLACE THE TABLETS DIRECTLY NEXT TO THE ROOT BALL, EVENLY DISTRIBUTED AROUND ITS PERIMETER, AT A DEPTH OF ABOUT 4 INCHES. PROOF OF COMPLIANCE WITH SPECIFICATIONS: THE CONTRACTOR WILL DEMONSTRATE COMPLIANCE BY SHOWING INVOICES TO PROVE PURCHASE OF PRODUCT IN SUFFICIENT QUANTITY TO COVER THE PROJECT AT THE RATES RECOMMENDED BY THE MANUFACTURER, INCLUDE PROJECT NAME, DATE OF PURCHASE OF PRODUCT, AND NAME OF CONTACT.

**NOTES:**


- THOROUGHLY SOAK THE GROUND COVER ROOT BALL AND ADJACENT PREPARED SOIL SEVERAL TIMES DURING THE FIRST MONTH AFTER PLANTING AND REGULARLY THROUGHOUT THE FOLLOWING TWO SUMMERS.
- SOIL AMENDMENTS:
  - MODIFY HEAVY CLAY OR SILT SOILS (MORE THAN 40% CLAY OR SILT) BY ADDING COMPOSTED PINE BARK (UP TO 30% BY VOLUME) OR GYPSUM
  - MODIFY EXTREMELY SANDY SOILS (MORE THAN 85% SAND) BY ADDING ORGANIC MATTER AND/OR DRY, SHREDDED CLAY LOAM UP TO 30% OF THE TOTAL MIX
- ALL GROUND COVER AREAS SHALL BE TREATED WITH A PRE-EMERGENT PER MANUFACTURER'S SPECIFICATIONS




SOIL CONDITION	MIN. WIDTH OF PREPARED SOIL (X)	TYPE OF PREPARATION
GOOD SOIL (NOT PREVIOUSLY GRADED OR COMPACTED, TOPSOIL LAYER INTACT)	6 FT. OR TWICE THE WIDTH OF THE ROOT BALL, WHICHEVER IS GREATER.	LOOSEN THE EXISTING SOILS TO THE WIDTHS AND DEPTHS SHOWN ON PLANTING DETAILS.
COMPACTED SOIL (NOT PREVIOUSLY GRADED, TOPSOIL LAYER DISTURBED BUT NOT ELIMINATED)	15 FT.	LOOSEN THE EXISTING SOILS TO THE WIDTHS AND DEPTHS SHOWN ON PLANTING DETAILS. ADD COMPOSTED ORGANIC MATTER TO BRING THE CONTENT UP TO 5% DRY WEIGHT.
GRADED SUBSOILS AND CLEAN FILLS WITH CLAY CONTENT BETWEEN 5 AND 35 %	20 FT.	MINIMUM TREATMENT: LOOSEN EXISTING SOILS TO WIDTHS AND DEPTHS SHOWN. ADD COMPOSTED ORGANIC MATTER TO BRING ORGANIC CONTENT UP TO 5 % DRY WEIGHT. OPTIMUM TREATMENT: REMOVE TOP 8 TO 10 IN. OR THE EXISTING MATERIAL. LOOSEN EXISTING SOILS TO THE WIDTHS AND DEPTHS SHOWN IN THE PLANTING DETAILS. ADD 8 -10 IN. OF LOAM TOPSOIL.
POOR QUALITY FILLS, HEAVY CLAY SOILS, SOILS CONTAMINATED WITH RUBBLE OR TOXIC MATERIAL	20 FT.	REMOVE EXISTING SOILS TO THE WIDTHS AND DEPTHS SHOWN, REPLACE WITH LOAM AND TOPSOIL.

**NOTES:**

- FOR THE CONTAINER-GROWN SHRUBS, USE FINGERS OR SMALL HAND TOOL TO PULL THE ROOTS OUT OF THE OUTER LAYER OF POTTING SOIL; THEN CUT OR PULL APART ANY ROOTS CIRCLING THE PERIMETER OF THE CONTAINER.
- THOROUGHLY SOAK THE SHRUB ROOT BALL AND ADJACENT PREPARED SOIL SEVERAL TIMES DURING THE FIRST MONTH AFTER PLANTING AND REGULARLY THROUGHOUT THE FOLLOWING TWO SUMMERS.
  - MODIFY HEAVY CLAY OR SILT SOILS (MORE THAN 40% CLAY OR SILT) BY ADDING COMPOSTED PINE BARK (UP TO 30% BY VOLUME) OR GYPSUM
  - MODIFY EXTREMELY SANDY SOILS (MORE THAN 85% SAND) BY ADDING ORGANIC MATTER AND/OR DRY, SHREDDED CLAY LOAM UP TO 30% OF THE TOTAL





**CLERESTORY PLAN**  
SCALE: 1/8" = 1'-0"

**ARCHITECTURAL FLOOR PLAN**  
SCALE: 1/8" = 1'-0"

FAR = (TOTAL BUILDING FLOOR AREA/ GROSS LOT AREA)  
7.5% = 3,803SF/ 51,016SF

**GENERAL FLOOR PLAN NOTES:**

- THIS DRAWING IS DIAGRAMMATIC AND SHOULD BE USED TO DETERMINE THE DESIGN INTENT. THE CONTRACTOR IS RESPONSIBLE FOR THE COMPLETE SET OF WORK AS INDICATED AND SHALL FIELD VERIFY ALL WORK, COORDINATE ALL DRAWINGS / NEW WORK AND SHALL NOTIFY ARCHITECT IMMEDIATELY OF ANY DISCREPANCIES IN THE DOCUMENTS BEFORE PROCEEDING. FAILURE TO DO SO WILL RESULT IN THE CONTRACTOR TAKING FULL RESPONSIBILITY AND LIABILITY FOR SAID DISCREPANCIES.
- ALL DIMENSIONS ARE SHOWN FROM FINISH FACE TO FINISH FACE OF PARTITION UNLESS OTHERWISE NOTED.
- WALL THICKNESS' ARE NOMINAL NOT ACTUAL DIMENSIONS. SEE WALL SCHEDULE FOR ACTUAL DIMENSIONS.
- ALL WOOD, INCLUDING BLOCKING, USED ON THE PROJECT SHALL BE FIRE RETARDANT TREATED.
- ALL WORK SHALL BE DONE IN ACCORDANCE WITH ALL LOCAL, STATE, COUNTY CODE REGULATIONS, O.S.H.A., AND THE AMERICAN WITH DISABILITIES ACT (ADA). REFER TO THE CODE PLAN FOR MORE INFORMATION.
- PROVIDE POSITIVE SLOPE TO ALL FLOOR DRAINS WHILE KEEPING FLOOR LEVEL AT WALL BASE CONDITION.
- PROVIDE TRANSITION STRIPS AT EACH CHANGE IN FLOOR FINISH MATERIALS.
- REINFORCE WALL AND PROVIDE BLOCKING AS REQUIRED TO SUPPORT WALL CABINETS AND COUNTERTOPS.
- THE CONTRACTOR SHALL PROVIDE AND INSTALL WALL REINFORCING FOR INSTALLATION OF ACCESSORIES, COAT RACKS, CHART RACKS, CASEWORK, AND OTHER WALL MOUNTED ITEMS.
- ALL EXPOSED PIPES, DUCTS, AND CONDUIT TO BE PAINTED TO MATCH EXISTING.
- PROVIDE CONTROL JOINTS IN GYPSUM BOARD PARTITIONS AT 30'-0" O.C. MAXIMUM AND AS INDICATED IN THE CONTRACT DOCUMENTS.
- COORDINATE WITH OWNER'S EQUIPMENT SUPPLIER FOR INSTALLATION REQUIREMENTS / LOCATIONS OF FLOOR / WALL / CEILING MOUNTED ITEMS; IE. CAMERAS, TVS, SPEAKERS, SENSORS, SECURITY WIRING, VAULTS, ATMS.
- CONTRACTOR SHALL CONDUCT A ROUGH ELECTRICAL INSPECTION WITH OWNER, PRIOR TO ENCLOSING WALLS, FOR THE PURPOSE OF CONFIRMING ALL J-BOX LOCATIONS FOR POWER, DATA, VOICE, SWITCH, THERMOSTAT, ETC.
- CONTRACTOR TO FILL ANY AND ALL EQUIPMENT PENETRATIONS OR DEPRESSIONS INTO OR THROUGH THE EXISTING SLAB THAT WILL NOT BE UTILIZED TO FEED NEW EQUIPMENT (I.E. ABANDONED FLOOR CORES, IMPRESSION FROM PREVIOUS EQUIPMENT FLOOR PLATE REMOVAL). PENETRATIONS SHALL BE FILLED WITH NON-SHRINK GROUT. THE SIDES OF ANY EXISTING OPENINGS SHALL BE MODIFIED/TAPERED SO THAT THEY ARE WIDER AT THE TOP THAN AT THE BOTTOM. FOR LARGE OPENINGS, PROVIDE ONE (1) #5 BAR 2" UP FROM BOTTOM OF HOLE.
- A TACTILE SIGN STATING 'EXIT' AND COMPLYING WITH ICC-A117.1 SHALL BE PROVIDED ADJACENT TO EACH DOOR TO AN 'AREA OF REFUGE', AN EXTERIOR AREA FOR ASSISTED RESCUE, AN EXIT STAIRWAY, AN EXIT RAMP, AN EXIT PASSAGEWAY, AND THE EXIT DISCHARGE.

**FLOOR PLAN KEY NOTES:**


- (TYPICAL THIS SHEET ONLY)
- 6'-8" WIDE SUPPORTED CONC. STOOP
  - VACUUM AIR TUBE SYSTEM; COOR UNIT LOCATIONS WITH LAYOUT OF ROOF STRUCTURE.
  - TACK BOARDS
  - PROVIDE FIVE (5) 1-1/2" THICK SHELVES; 18" DEEP W/ WHITE P LAM FINISH, VERT. K.V. STANDARDS & BRACKETS FL TO CEILING @ 16" O.C. HORIZ.
  - SECURITY KEY BOX - VERIFY WITH FIRE MARSHAL EXACT PRODUCT REQUIRED (MANUF - KNOX BOX).
  - SUNSHADE CANOPY ABOVE WINDOWS ONLY. SEE ROOF PLAN FOR ADDITIONAL INFORMATION.
  - ATM DRIVE-UP KIOSK WITH VALANCE AND POINT-TO POINT VAT SYSTEM BY OWNER'S BANK EQUIPMENT VENDOR; CONTRACTOR TO COORDINATE INSTALLATION.
  - STEEL ROOF LADDER.
  - ELECTRICAL METER AND CT CABINET; PAINT TO MATCH MASONRY COLOR.
  - GAS METER; GAS PIPING TO BE RUN IN WALL CAVITY.
  - ELECTRICAL / DATA OUTLETS TO BE CENTERED BETWEEN WINDOWS; COOR W/ FURNITURE.
  - AUTOMATIC DOOR OPERATOR BARRIER FREE PUSH-BUTTON
  - WATER HEATER ON OVERHEAD PLATFORM. SEE PLUMBING DRAWINGS FOR ADDITIONAL INFORMATION.
  - OUTLINE OF CLERESTORY / SOFFIT ABOVE.
  - TRANSFORMER ON CONCRETE PAD; COORDINATE WITH ELECTRICAL TRADES.
  - TRANSFORMER CLEARANCE; COORDINATE WITH ELECTRICAL TRADES.
  - BARRIER FREE COMPLIANT HI / LOW DRINKING FOUNTAIN.
  - REFER TO SITE DRAWINGS FOR ADDITIONAL DRIVE-THRU PAVING REQUIREMENTS.
  - PROVIDE 3/4" PLYWOOD BACKER FOR WALL MOUNTED BINDER BINS. COORDINATE EXACT LOCATIONS WITH FURNITURE LAYOUT.
  - ALL ELECTRICAL/LOW VOLTAGE INSTALLED SERVICE OUTLETS TO BE RUN UNDERGROUND/UNDERFLOOR (SEE ELECTRICAL ENGINEERING DRAWINGS).
  - 1/2" THICK GLASS IN ANODIZED ALUMINUM FRAMES FOR OFFICE WALLS AS ILLUSTRATED.
  - PROVIDE CUSTOM PL-1 LAMINATE PASS-THRU TRIM (BOTH SIDES AND SOFFIT ABOVE) AT OPENING AS ILLUSTRATED. OVERLAP TRIM 2" ON ALL SIDES TO MATCH DOOR FRAME SIMILAR WIDTH. REFER TO MILLWORK DETAILS FOR FURTHER INFORMATION.
  - PRE-MANUFACTURE DECORATIVE FURNITURE WALL PARTITION SYSTEM. WALL TO HAVE 42" HIGH FABRIC WALL COVERING WITH 15" HIGH GLASS PARTITION BEARING ON WALL. COORDINATE WITH FURNITURE MANUFACTURE.



**STUCKY VITALE ARCHITECTS**  
27172 WOODWARD AVENUE  
ROYAL OAK, MI 48067-0925  
P. 248.546.6700  
F. 248.546.8454  
WWW.STUCKYVITALE.COM

STATEMENT OF INTELLECTUAL PROPERTY:  
THE IDEAS, CONCEPTS, DRAWINGS AND THOUGHTS CONVEYED HEREIN ARE THE INTELLECTUAL PROPERTY OF STUCKY VITALE ARCHITECTS. THIS SET OF DRAWINGS, IN WHOLE OR IN PART, MAY NOT BE REPRODUCED, WITHOUT THE WRITTEN CONSENT OF STUCKY VITALE ARCHITECTS. THIS INFORMATION IS PROTECTED UNDER U.S. COPYRIGHT LAW, ALL RIGHTS RESERVED.

Consultants:



Project:  
**MICHIGAN SCHOOLS + GOVERNMENT CREDIT UNION - NEW BUILD**  
2151 W. STADIUM BLVD.  
ANN ARBOR, MI

Issued for:

SITE PLAN APPROVAL	05.30.19
SITE PLAN APPROVAL REVISIONS	08.15.19
SITE PLAN APPROVAL REVISIONS	10.11.19
REVISIONS PER 3RD PLAN COMMENTS	10.28.19

Drawn by:  
RBG  
Checked by:  
MJB

Sheet Title:  
**ARCHITECTURAL FLOOR PLAN**

Project No.:  
**2018.157**

Sheet No.:  
**A1.1**

DO NOT SCALE DRAWINGS © 2018 StuckyVitale Architects






**STUCKY VITALE ARCHITECTS**  
 27172 WOODWARD AVENUE  
 ROYAL OAK, MI 48067-0925  
 P. 248.546.6700  
 F. 248.546.8454  
 WWW.STUCKYVITALE.COM

STATEMENT OF INTELLECTUAL PROPERTY:  
 THE IDEAS, CONCEPTS, DRAWINGS AND THOUGHTS  
 CONVEYED HEREIN ARE THE INTELLECTUAL  
 PROPERTY OF STUCKY VITALE ARCHITECTS. THIS SET  
 OF DRAWINGS, IN WHOLE OR IN PART, MAY NOT BE  
 REPRODUCED, WITHOUT THE WRITTEN CONSENT OF  
 STUCKY VITALE ARCHITECTS. THIS INFORMATION IS  
 PROTECTED UNDER U.S. COPYRIGHT LAW. ALL  
 RIGHTS RESERVED.

Consultants:



Project:  
 MICHIGAN SCHOOLS  
 + GOVERNMENT CREDIT  
 UNION - NEW BUILD  
 2151 W. STADIUM BLVD.  
 ANN ARBOR, MI

Issued for:  
 SITE PLAN  
 APPROVAL 05.30.19  
 SITE PLAN APPROVAL  
 REVISIONS 10.11.19  
 REVISIONS PER 3RD PLAN'G  
 COMMENTS 10.2819

Drawn by:  
 RBG  
 Checked by:  
 MJB  
 Sheet Title:  
 EXTERIOR  
 ELEVATIONS

Project No. :  
 2018.157

Sheet No. :  
 A3.1


DO NOT SCALE DRAWINGS  
 © 2018 Stucky Vitale Architects

**ELEVATION KEY NOTES:**


- 1 PREFINISHED METAL COPING SYSTEM. COLOR TO BE SILVER METALLIC.
- 2 PAINTED METAL COPING EXTENDER WITH OFFSET AND A 1/4" DRIP EDGE; COLOR TO MATCH, PMS 209C
- 3 CAST STONE VENEER SYSTEM - SMOOTH (CS-1) 8"x16" W/ 1/4" JOINT
- 4 PRE-FINISHED KAWNEER OUTRIGGER SUNSHADE BLADE SYSTEM. POWDER COAT FINISH TO MATCH BURGANDY PMS 209C
- 5 CAST STONE VENEER SYSTEM - SPLIT FACE (CS-2) 8"x16" W/ 1/4" JOINT
- 6 4" CAST STONE SILL (SL325)
- 7 8" CAST STONE SILL (SL 375)
- 8 CAST STONE WALL CAP
- 9 STOREFRONT SYSTEM, REFER TO WINDOW TYPES
- 10 AUTOMATIC ENTRANCE DOOR PUSH-BUTTON
- 11 WALL SCONCE LIGHT FIXTURE
- 12 PREFINISHED METAL CLAD CANOPY
- 13 PAINTED METAL ACCENT BAND. COLOR TO MATCH PMS 209C
- 14 PREFINISHED FLUSH METAL PANEL SYSTEM
- 15 PREFINISHED CORRUGATED METAL WALL PANEL ROOF TOP EQUIPMENT SCREEN
- 16 LANE INDICATOR SIGNS, SEMI-RECESSED
- 17 PACKAGE RECEIVER M.O.; PAINTED
- 18 NIGHT DEPOSIT M.O.
- 19 ATM KIOSK W/ VALANCE; CONTR TO COOR INSTALLATION
- 20 BULLET-RESISTANT WINDOW BY OTHERS; CONTRACTOR TO COORDINATE INSTALL
- 21 OVERFLOW ROOF DRAIN SPOUT WITH RODENT SCREEN; PAINT INTERIOR PIPE BLACK
- 22 RECESSED HOSE BIBB
- 23 NOT USED
- 24 NOT USED
- 25 COMPOSITE WOOD FACED GATE WITH GALV FLUSH BOLT & STL SLEAVES IN CONCRETE
- 26 CONCRETE FOUNDATION @ 42" BELOW FIN GRADE; MIN
- 27 SUPPORTED STOOP
- 28 J-BOX BY CONTRACTOR FOR SECURITY CAMERA BY OTHERS; COOR. LOCATION WITH SECURITY CONTRACTOR.
- 29 PREFINISHED METAL PIER CAP.
- 30 PREFINISHED METAL COUNTERFLASHING
- 31 VAT SYSTEM BY OTHERS; CONTRACTOR TO COORDINATE INSTALLATION.
- 32 CPI DAYLIGHTING SYSTEM.
- 33 TEMPORARY BANNER - NOW OPEN!
- 34 READING ROCK CAST STONE 24 X 26 (SMOOTH ST2436)
- 35 10'x4' AREA TO BE A DIRECT APPLIED FINISH SYSTEM WITH A SMOOTH FINISH. AREA TO BE AN EXTERIOR MARKETING BOARD.

COLOR TO MATCH PMS 209C


READING ROCK CAST STONE WHEATSTONE (SMOOTH) ST2436/ ST015



**3 WEST ELEVATION**  
 A3.1 SCALE: 1/4" = 1'-0"  
 WITH CANOPY




**2 WEST ELEVATION**  
 A3.1 SCALE: 1/4" = 1'-0"  
 WITHOUT CANOPY



**1 NORTH ELEVATION**  
 A3.1 SCALE: 1/4" = 1'-0"

DO NOT SCALE DRAWINGS  
 © 2018 Stucky Vitale Architects




- ELEVATION KEY NOTES:**
- 1 PREFINISHED METAL COPING SYSTEM. COLOR TO BE SILVER METALLIC.
  - 2 PAINTED METAL COPING EXTENDER WITH OFFSET AND A 1/4" DRIP EDGE; COLOR: TO MATCH, PMS 209C
  - 3 CAST STONE VENEER SYSTEM - SMOOTH (CS-1) 8"x16" W/ 1/4" JOINT
  - 4 PRE-FINISHED KAWNEER OUTRIGGER SUNSHADE BLADE SYSTEM. POWDER COAT FINISH TO MATCH BURGANDY PMS 209C
  - 5 CAST STONE VENEER SYSTEM - SPLIT FACE (CS-2) 8"x16" W/ 1/4" JOINT
  - 6 4" CAST STONE SILL (SL325)
  - 7 8" CAST STONE SILL (SL 375)
  - 8 CAST STONE WALL CAP
  - 9 STOREFRONT SYSTEM, REFER TO WINDOW TYPES
  - 10 AUTOMATIC ENTRANCE DOOR PUSH-BUTTON
  - 11 WALL SCONCE LIGHT FIXTURE
  - 12 PREFINISHED METAL CLAD CANOPY
  - 13 PAINTED METAL ACCENT BAND. COLOR TO MATCH PMS 209C
  - 14 PREFINISHED FLUSH METAL PANEL SYSTEM
  - 15 PREFINISHED CORRUGATED METAL WALL PANEL ROOF TOP EQUIPMENT SCREEN
  - 16 LANE INDICATOR SIGNS, SEMI-RECESSED
  - 17 PACKAGE RECEIVER M.O.; PAINTED
  - 18 NIGHT DEPOSIT M.O.
  - 19 ATM KIOSK W/ VALANCE; CONTR TO COOR INSTALLATION
  - 20 BULLET-RESISTANT WINDOW BY OTHERS; CONTRACTOR TO COORDINATE INSTALL
  - 21 OVERFLOW ROOF DRAIN SPOUT WITH RODENT SCREEN; PAINT INTERIOR PIPE BLACK
  - 22 RECESSED HOSE BIBB
  - 23 WALL SIGN - SEE 11/A2.1 FOR DIMENSIONS
  - 24 8" PIN MOUNTED BUILDING ADDRESS
  - 25 COMPOSITE WOOD FACED GATE WITH GALV FLUSH BOLT & STL SLEAVES IN CONCRETE
  - 26 CONCRETE FOUNDATION @ 42" BELOW FIN GRADE; MIN
  - 27 SUPPORTED STOOP
  - 28 J-BOX BY CONTRACTOR FOR SECURITY CAMERA BY OTHERS; COOR. LOCATION WITH SECURITY CONTRACTOR.
  - 29 PREFINISHED METAL PIER CAP.
  - 30 PREFINISHED METAL COUNTERFLASHING
  - 31 VAT SYSTEM BY OTHERS; CONTRACTOR TO COORDINATE INSTALLATION.
  - 32 CPI DAYLIGHTING SYSTEM.
  - 33 TEMPORARY BANNER - NOW OPEN!
  - 34 READING ROCK CAST STONE 24 X 26 (SMOOTH ST2436)
  - 35 10"x4" AREA TO BE A DIRECT APPLIED FINISH SYSTEM WITH A SMOOTH FINISH. AREA TO BE AN EXTERIOR MARKETING BOARD.

**SVA**  
**STUCKY VITALE ARCHITECTS**  
 27172 WOODWARD AVENUE  
 ROYAL OAK, MI 48067-0925  
 P. 248.546.6700  
 F. 248.546.8454  
 WWW.STUCKYVITALE.COM

STATEMENT OF INTELLECTUAL PROPERTY:  
 THE IDEAS, CONCEPTS, DRAWINGS AND THOUGHTS  
 CONVEYED HEREIN ARE THE INTELLECTUAL  
 PROPERTY OF STUCKY VITALE ARCHITECTS. THIS SET  
 OF DRAWINGS, IN WHOLE OR IN PART, MAY NOT BE  
 REPRODUCED, WITHOUT THE WRITTEN CONSENT OF  
 STUCKY VITALE ARCHITECTS. THIS INFORMATION IS  
 PROTECTED UNDER U.S. COPYRIGHT LAW. ALL  
 RIGHTS RESERVED

Consultants:



Project:  
 MICHIGAN SCHOOLS  
 + GOVERNMENT CREDIT  
 UNION - NEW BUILD  
 2151 W. STADIUM BLVD.  
 ANN ARBOR, MI

Issued for:  
 SITE PLAN  
 APPROVAL 05.30.19  
 SITE PLAN APPROVAL  
 REVISIONS 10.11.19  
 REVISIONS PER 3RD PLAN'G  
 COMMENTS 10.2819

Drawn by:  
 RBG  
 Checked by:  
 MJB

Sheet Title:  
 EXTERIOR  
 ELEVATIONS

Project No. :  
**2018.157**

Sheet No. :  
**A3.2**

DO NOT SCALE DRAWINGS © 2018 Stucky Vitale Architects



2018.157 - MSGCU ANN ARBOR - CONCEPTUAL DESIGN RENDERING - OCTOBER 11TH, 2019  
 RENDERING BY ROB GURCHE - STUCKY VITALE ARCHITECTS



STUCKY VITALE ARCHITECTS  
 27172 WOODWARD AVENUE  
 ROYAL OAK, MI 48067-0925  
 P. 248.546.6700  
 F. 248.546.8454  
 WWW.STUCKYVITALE.COM

STATEMENT OF INTELLECTUAL PROPERTY:  
 THE IDEAS, CONCEPTS, DRAWINGS AND THOUGHTS  
 CONVEYED HEREIN ARE THE INTELLECTUAL  
 PROPERTY OF STUCKY VITALE ARCHITECTS. THIS SET  
 OF DRAWINGS, IN WHOLE OR IN PART, MAY NOT BE  
 REPRODUCED, WITHOUT THE WRITTEN CONSENT OF  
 STUCKY VITALE ARCHITECTS. THIS INFORMATION IS  
 PROTECTED UNDER U.S. COPYRIGHT LAW. ALL  
 RIGHTS RESERVED.

Consultants:

Project :

MICHIGAN SCHOOLS  
 + GOVERNMENT CREDIT  
 UNION - NEW BUILD  
 2151 W. STADIUM BLVD.  
 ANN ARBOR, MI

Issued for :

SITE PLAN	
APPROVAL	05.30.19
SITE PLAN APPROVAL	
REVISIONS	10.11.19
REVISIONS PER 3RD PLAN'G	
COMMENTS	10.2819

Drawn by :  
 RBG  
 Checked by :  
 MJB

Sheet Title :  
 EXTERIOR RENDERING

Project No. :  
 2018.157

Sheet No. :  
 A3.3

DO NOT SCALE DRAWINGS  
 ©2018 Stucky Vitale Architects